







回路番号
(タイプA: 番号1
タイプB: 極数末尾番号)

一般公差	
10以下	± 0.2
10を越え30以下	± 0.25
30を越え100以下	± 0.3
角 度	± 3°



パネル取付寸法 △
(公差: ±0.1)



- 注: △ 6 OBSOLETE PARTS: OBSOLETE CIS STREAMLINING PER D.RENAUD/D.SINISI
- △ 2 極品Kのみ適用
- △ 1 適用パネル厚寸法 0.8~1.6 mm.
2. ハウジングはパネル打抜き側から挿入すること。
3. 適用コネクタ型番 170376 (AWG #20-26)
170377 (AWG #26-30)
4. 適用製品規格: 108-5118

B (逆回路)	171880	↑	18.2	22	23.5 (12)	↑	↑	15	16.1	17.9	6	4-	↑	-6	2-	↑	-6	↑	-6
		↑	15.7	19.5	21 (9.5)	↑	↑	12.5	13.6	15.4	5	4-	↑	-5	2-	↑	-5	↑	-5
		↑	13.2	17	18.5 (7)	↑	↑	10	11.1	12.9	4	4-	↑	-4	2-	↑	-4	↑	-4
		4.2	10.7	14.5	16 (4.5)	2.5	4	7.5	8.6	10.4	3	△4	↑	-3	2-	↑	-3	↑	-3
		3.7	8.2	12	13.5 (2)	2	3.5	5	6.1	7.9	2	4-172214-2	2-172214-2	172214-2					
A (標準)	171822	↑	23.2	27	28.5 (17)	↑	↑	20	21.1	22.9	8	↑	↑	↑	-8				
		↑	20.7	24.5	26 (14.5)	↑	↑	17.5	18.6	20.4	7	↑	↑	2-	↑	-7	↑	-7	
		↑	10.2	22	23.5 (12)	↑	↑	15	16.1	17.9	6	4-	↑	-6	2-	↑	-6	↑	-6
		↑	15.7	19.5	21 (9.5)	↑	↑	12.5	13.6	15.4	5	4-	↑	-5	2-	↑	-5	↑	-5
		↑	13.2	17	18.5 (7)	↑	↑	10	11.1	12.9	4	4-	↑	-4	2-	↑	-4	↑	-4
		4.2	10.7	14.5	16 (4.5)	2.5	4	7.5	8.6	10.4	3	4-	↑	-3	2-	↑	-3	↑	-3
		3.7	8.2	12	13.5 (2)	2	3.5	5	6.1	7.9	2	4-172213-2	2-172213-2	172213-2					
		↑	23.2	27	28.5 (17)	↑	↑	20	21.1	22.9	8	↑	↑	↑	-8				
回路番号 タイプ	指令相手 ハウジング型番	K	J	H	G	F	E	D	C	B	A	極数	青色	黒色	自然色				
寸 法												型 番							