



断面 A-A
SECT.

二重ロック時
DOUBLE LOCKED

LTR	REVISION RECORD	DR	CHK	DATE
B	REVISED F400-0507-93	CS	KO	5/10
A	REVISED F400-0460-93	S.S	KO	5/10
O	RELEASED	KB	YM	5/15

Copyright ©1988 AMP (Japan), LTD. ALL RIGHTS RESERVED.	Copyright ©1988 AMP (Japan), LTD. ALL RIGHTS RESERVED.
適用電線 (WIRE RANGED)	適用絶縁体 (INSULATION DIA.)
材料 (MATERIAL)	色 (COLOR)
PBT	参照表 SEE TABLE
DR. C. TAGUCHI	DE. S. Oguma
CHK. S. Matsuda	APP. N. Nishida

色 (COLOR)	製品型番 (PART NO.)
青 (BLUE)	174967-5
緑 (GREEN)	174967-4
黒 (BLACK)	174967-2

- NOTE,
- △ TO BE MEASURED WITHIN 2mm FROM [Z-]
 - △ THE MATING PLUG HOUSING PART NUMBER: 174966
 - △ APPLICABLE CONTACT PART NUMBER: 173682
- 注:
- △ [Z-] 面から 2mmの範囲で測定。
 - △ 相手側ハウジング型番: 174966
 - △ 適用端子型番: 173682

CUSTOMER DRAWING 参考図面

AMP AMP (JAPAN), LTD.
Tokyo, Japan

4 POS. CAP HOUSING, .040 SERIES MULTI-LOCK CONNECTOR
一般公差 (GENERAL TOLERANCES)
0<K<10: ±0.2
10<K<30: ±0.25
30<K<100: ±0.3
角度 (ANGLES): ±0.5°

SIZE LOC 番号 (NUMBER)
C J C-174967
尺規 (SCALE) REV. SHEET
2-1 B 1 OF 1