












► Deviation List

Hood Lock Screw	Straight Hood for 9, 15, 25, 37 contact 	Right Angle Hood for 25 contact 	Hood Lock Screw	Straight Hood for Slim Cable 9,15, 25, 37 contact 															
17J-001 □  24	Hood P/N: 17JE-25H-1A-CF 25 contact Thread Size: A Deviation: (D8 □) (※) • Socket 17JE-13 □ □ 0-02(D8 □)A-CG • Pin 17JE-23 □ □ 0-02(D8 □)-CG		17J-001 □  24	Hood P/N: 17JE- □ □ H2- □ □ -CF Deviation: (D8 □) (※) • Socket 17JE-33 □ □ 0-02(D8 □)A-CG • Pin 17JE-43 □ □ 0-02(D8 □)-CG															
17J-002 □  6.5 24	Hood P/N: 17JE- □ □ H-1 □ 2-CF Deviation: (D8 □ 2) (※) • Socket 17JE-13 □ □ 0-02(D8 □ 2)A-CG • Pin 17JE-23 □ □ 0-02(D8 □ 2)-CG		17J-002 □  6.5 24	Hood P/N: 17JE- □ □ H2- □ □ 2-CF Deviation: (D8 □ 2) (※) • Socket 17JE-33 □ □ 0-02(D8 □ 2)A-CG • Pin 17JE-43 □ □ 0-02(D8 □ 2)-CG															
17J-005 □ -CF  10 42.9	Hood P/N: 17JE- □ □ H-1 □ 4-CF Deviation: (D8 □ 6) (※) • Socket 17JE-13 □ □ 0-02(D8 □ 6)A-CG • Pin 17JE-23 □ □ 0-02(D8 □ 6)-CG		17J-005 □ -CF  10 42.9	17JE- □ □ H2- □ □ 4-CF Deviation: (D8 □ 6) (※) • Socket 17JE-33 □ □ 0-02(D8 □ 6)A-CG • Pin 17JE-23 □ □ 0-02(D8 □ 6)-CG															
17J-008 □ -CF  6.5 20		Hood P/N: 17JE-25LH-1 □ -CF Deviation: (D18 □) (※) • Socket 17JE-13 □ □ 0-02(D18 □)A-CG • Pin 17JE-23 □ □ 0-02(D18 □)-CG	Applicable Cable Size <table><thead><tr><th>Size</th><th>Standard Cable</th><th>Slim Cable</th></tr></thead><tbody><tr><td>9</td><td>φ 7.0 (max.)</td><td>φ 5.1 (max.)</td></tr><tr><td>15</td><td>φ 8.0 (max.)</td><td>φ 5.7 (max.)</td></tr><tr><td>25</td><td>φ 9.0 (max.)</td><td>φ 6.6 (max.)</td></tr><tr><td>37</td><td>φ 10.5 (max.)</td><td>φ 7.4 (max.)</td></tr></tbody></table>		Size	Standard Cable	Slim Cable	9	φ 7.0 (max.)	φ 5.1 (max.)	15	φ 8.0 (max.)	φ 5.7 (max.)	25	φ 9.0 (max.)	φ 6.6 (max.)	37	φ 10.5 (max.)	φ 7.4 (max.)
Size	Standard Cable	Slim Cable																	
9	φ 7.0 (max.)	φ 5.1 (max.)																	
15	φ 8.0 (max.)	φ 5.7 (max.)																	
25	φ 9.0 (max.)	φ 6.6 (max.)																	
37	φ 10.5 (max.)	φ 7.4 (max.)																	
17J-014 □ -CF  6.5 19		Hood P/N: 17JE-25LH-1 □ 1-CF Deviation: (D18 □ 1) (※) • Socket 17JE-13 □ □ 0-02(D18 □ 1)A-CG • Pin 17JE-23 □ □ 0-02(D18 □ 1)-CG																	

Thread Size

A : M2.6×0.45

B : M3×0.5

C : # 4-40UNC

not available

(※) Connector with Hood Kit

© Specifications and/or dimensions in this catalogue are subject to change without notice.
Your catalogue checking the latest specifications with our drawings would be highly appreciated.