

Prototyping board accessories

Single sided pin (Type 10)

For use with plain or copper-clad boards. These pins have the facility for soldering discrete components on one side and wire wrapping on the other.

Material: Manufactured from phosphor bronze to BS 2870 PB 102 with tin finish over copper flash.

Post size: 0,68 mm x 0,64 mm, diagonal 0,94 mm

d Pin	Ordering information	
Compatible hole Ø pierced/drilled	Order code	
1,00/1,05	18-0226	
	Compatible hole Ø pierced/drilled	

Supplied in packets of 500

Double sided pin (Type 11)

For use when wirewrapping is required both sides of the board.

Type Compatible hole Ø pierced/drilled	Order code	
11 1,00/1,05	18-1657	

Supplied in packets of 500

Solder Terminal Pin

Solder terminal pin (Type 2)

By inserting pin up to its shoulder these pins stand at a fixed height above the board surface. The separated profile offers good mechanical retention while electrical contact is made by soldering shoulder to copper track.

Available in two sizes for hole size 1,02 and 1,32 mm.

Ooldor lolli	iiiiai i iii					Ordoning information
Ilolo dio		D	Order code			
Hole dia.	Α	В	С	D	Е	Order code
1,00	9,7	5,6	1,1	1,0	0,4	18-0222
1 22	11.0	6.7	1 /	1 2	0.5	18_0210

Ordering information

Supplied in packets of 1000

Solder terminal pin (Type 3)

Similar to 18-0222D but manufactured from phosphor bronze to BS 2873 PB 102, tin finish over copper flash.

Solder Terminal Pin	Ordering information		
Туре	Qty	Hole dia.	Order code
3	1000	1,00	18-0218

Solder terminal half pin (Type 4)

These pins are ideally suited to take off points or flying leads from a PCB. The shoulder is soldered to the copper track with the pin protruding on the component side of the board. Two sizes are available for 1,02 and 1,32 mm diameter holes.

Solder Terminal Half Pin

Ordering information

Coldor Tollinia			0	ading internation
Туре	Qty	Hole dia.	Dim.A	Order code
4	1000	1,32	1,21	18-0217
4	1000	1,00	0,93	18-0223

