

#### **FEATURES**

- Excellent electrical connection
- Reduces short circuits
- Tin plated copper tube for excellent conductivity
- Crimped terminal can be repeatedly inserted and removed without degrading end of the wire

# RS PRO Crimp Bootlace Ferrule, 10mm Pin Length, 2.6mm Pin Diameter, 2.5mm<sup>2</sup> Wire Size

RS Stock No.: 211-4296



RS Professionally Approved Products bring to you professional quality parts across all product categories. Our product range has been tested by engineers and provides a comparable quality to the leading brands without paying a premium price.



#### **Product Description**

From RS PRO a range of high-quality French colour coded bootlace ferrules (also known as cord end terminals) for providing a clean end termination to multi-stranded wires. These reliable wire ferrules ensure that you have a positive connection when connecting wires to terminal blocks and captive terminals

#### **Suitable Crimping Tools**

For ferrules with a wire size range of 0.25 to 6 mm<sup>2</sup> use crimping tool frame stock number 848-391 with crimping die 848-420

#### **General Specifications**

Number of Entries	1
Insulation	Uninsulated
Contact Material	Copper
Contact Plating	Tin
Terminal Material	Copper tube
Surface Treatment	Tin plate
Ferrule Type	French
Pack Quantity	10
Application	Bootlace ferrules are used on multi-stranded wires that are being inserted into screw terminals and terminal blocks. Applications include consumer units, circuit breakers, electrical control panels and any equipment where there is a requirement for a multi-stranded wire connection

### **Electrical Specifications**

Current Rating	9A
Voltage Rating	600V



## **Mechanical Specifications**

Maximum Wire Size (mm2)	2.5
Maximum Wire Size (AWG)	14
Pin Diameter	2.6mm
Pin Length	10mm
Overall Length	10mm
Weight	0.0520kg

## **Operation Environment Specifications**


Maximum Temperature	105°C
•	

## **Approvals**

Compliance/Certifications	CE / UR / cUR









L (mm)	D (mm)	C (mm)	W (mm)
10	2.6	2.3	3.3