

**211CC2S1160P : Sicma-3Plus Female  
1.5 mm Terminal**



ACTIVE



[www.fci.com](http://www.fci.com)

**Mating Half**

211CL2S1160

**Specifications**

<b>General</b>	
<b>Product Type</b>	Terminal system
<b>Terminal size (in mm)</b>	1.5
<b>Family</b>	Sicma
<b>Features</b>	Improved version of traditional 211CC2S1160 Suitable for secondary lock Low contact mating force One piece construction High current carrying capacity Class 125°C Smooth and rounded edges for mat seal application SICMA 3Plus
<b>Dimensional</b>	
<b>Wire size range Min - Max</b>	0.35 - 0.75 mm <sup>2</sup>
<b>Pitch</b>	3.5 mm
<b>Electrical</b>	
<b>Current Carrying Capacity at 23°C</b>	19A
<b>Current Carrying Capacity at 85°C</b>	13A
<b>Current Carrying Capacity at 100°C</b>	10A
<b>Maximum Insulation (in mm)</b>	18
<b>Resistance (Contact)</b>	< 2 mohms
<b>Mechanical</b>	
<b>Contact mating force</b>	< 4N
<b>Single Wire Seal Compatible</b>	No
<b>Contact unmating force</b>	< 3N
<b>Physical</b>	
<b>Plating</b>	Sn
<b>Material</b>	CuFe
<b>Environmental</b>	
<b>IMDS</b>	Yes
<b>Other Features</b>	
<b>Market</b>	Passenger Vehicles
<b>Type</b>	Female
<b>Crimping Tool</b>	211S025 8516,5426

<b>Tradename</b>	Sicma
<b>Disclaimer</b>	Displayed data is for information purposes only. For more information, please contact your local sales office. The supply of some products might be limited to some customers.