

Plug SLS205-L...


In-line, Ø 2 mm with spring-loaded MULTILAM for self-assembly of test leads.

Solder connection.

SLS205-L



SLS205-L/N



Order No.	Type	Rated voltage/current	Cable (A)			*Standard colors
22.2618-*	SLS205-L	AC 30 V / 10 A DC 60 V / 10 A	max. Ø 2.1 mm	0.5 mm ²	Au	21 22 23 24 25 26 27 28 29
22.2619-*	SLS205-L/N	AC 30 V / 10 A DC 60 V / 10 A	max. Ø 2.1 mm	0.5 mm ²	Ni	21 22 23 24 25 26 27 28 29

Component parts

22.2010-*	KT2-S	Connection sleeve
22.1009	LS205-L	Plug for SLS205-L
22.5029	LS205-L/N	Plug for SLS205-L/N



Assembly instructions MA136


www.staubli.com/electrical

Plug SL205-LA

In-line, Ø 2 mm, with spring-loaded MULTILAM, for self-assembly of test leads.

With rigid insulating sleeve.

Crimp or solder connection.



Order No.	Type	Rated voltage/current	Cable (A)			*Standard colors
65.3309-*	SL205-LA	600 V, CAT II / 10 A	max. Ø 2.7 mm	0.5 mm ²	Au	21 22



Assembly instructions MAH544

www.staubli.com/electrical



Optional colors 23 24 25 29

Further information, page 6