

CXW SERIES

NEW

◆ FEATURES

- Load Life : 105°C 5000 hours.
- Body diameter of ϕ 10mm to ϕ 18mm with high ripple current capability.
- This series is smaller and longer life than the current KXW series.
- RoHS compliance.



◆ SPECIFICATIONS

Items	Characteristics							
Category Temperature Range	-25 ~ +105°C							
Rated Voltage Range	400, 420, 450V.DC							
Capacitance Tolerance	$\pm 20\%$ (20°C, 120Hz)							
Leakage Current(MAX)	$I = 3\sqrt{CV}$ (After 5 minutes application of rated voltage) I = Leakage Current(μA) C = Rated Capacitance(μF) V = Rated Voltage(V)							
Dissipation Factor(MAX) (tanδ)	<table border="1"> <tr> <td>Rated Voltage (V)</td> <td>400~450</td> </tr> <tr> <td>tanδ</td> <td>0.2</td> </tr> </table>	Rated Voltage (V)	400~450	tanδ	0.2	(20°C, 120Hz)		
Rated Voltage (V)	400~450							
tanδ	0.2							
Endurance	After applying rated voltage with rated ripple current for 5000hrs at 105°C, the capacitors shall meet the following requirements. <table border="1"> <tr> <td>Capacitance Change</td> <td>Within $\pm 20\%$ of the initial value.</td> </tr> <tr> <td>Dissipation Factor</td> <td>Not more than 200% of the specified value.</td> </tr> <tr> <td>Leakage Current</td> <td>Not more than the specified value.</td> </tr> </table>		Capacitance Change	Within $\pm 20\%$ of the initial value.	Dissipation Factor	Not more than 200% of the specified value.	Leakage Current	Not more than the specified value.
Capacitance Change	Within $\pm 20\%$ of the initial value.							
Dissipation Factor	Not more than 200% of the specified value.							
Leakage Current	Not more than the specified value.							
Impedance Ratio(MAX)	<table border="1"> <tr> <td>Rated Voltage (V)</td> <td>400~450</td> </tr> <tr> <td>$Z(-25^\circ\text{C})/Z(20^\circ\text{C})$</td> <td>8</td> </tr> </table>	Rated Voltage (V)	400~450	$Z(-25^\circ\text{C})/Z(20^\circ\text{C})$	8	(120Hz)		
Rated Voltage (V)	400~450							
$Z(-25^\circ\text{C})/Z(20^\circ\text{C})$	8							

◆ MULTIPLIER FOR RIPPLE CURRENT

Frequency coefficient

Frequency(Hz)	60	120	500	1k	10k \leq
Coefficient	0.8	1.00	1.25	1.40	1.50

◆ PART NUMBER

□□□ — CXW — □□□ — □ — EFC — □□ — D×L
 Rated Voltage Series Rated Capacitance Capacitance Tolerance Option Lead Forming Case Size

◆DIMENSIONS

(mm)

ϕD	10	12.5	14.5	16	18
ϕd	0.6			0.8	
F	5.0			7.5	
α	2.0				

◆STANDARD SIZE

Cap (μF)	WV	400					420				
		$\phi 10$	$\phi 12.5$	$\phi 14.5$	$\phi 16$	$\phi 18$	$\phi 10$	$\phi 12.5$	$\phi 14.5$	$\phi 16$	$\phi 18$
39	10×40	0.37					10×40	0.36			
47	10×45	0.42					10×50	0.43			
56	10×50	0.47						12.5×40	0.48		
68		12.5×40	0.54					12.5×40	0.52	14.5×31.5	0.52
82		12.5×45	0.61	14.5×31.5	0.57			12.5×45	0.59	14.5×35	0.59
100		12.5×50	0.68	14.5×40	0.69	16×31.5	0.71			14.5×40	0.67
120			14.5×45	0.79	16×35	0.80			14.5×45	0.75	16×35
150				16×40	0.92	18×31.5	0.89			16×45	0.94
180				16×50	1.08	18×40	1.06			16×50	1.05
220					18×45	1.20				18×50	1.22

Cap (μF)	WV	450				
		$\phi 10$	$\phi 12.5$	$\phi 14.5$	$\phi 16$	$\phi 18$
33	10×40	0.34		-	-	-
39	10×45	0.38				
47		12.5×40	0.44			
56		12.5×40	0.49			
68		12.5×45	0.55	14.5×31.5	0.52	
82		12.5×50	0.62	14.5×40	0.63	16×31.5
100			14.5×45	0.71	16×35	0.73
120			14.5×50	0.79	16×40	0.82
150				16×50	0.98	18×40
180					18×45	1.09
220					18×50	1.22

Size $\phi D \times L$ (mm)

Ripple Current (A r.m.s./105°C, 120Hz)