



ENGLISH

Datasheet

**RS Pro Clear Heat Shrink Tubing sleeve diameter 3.2mm
length 30cm ratio 2:1**

RS Stock No: **458-0667**



Product Details

RS Pro heat shrink tubing sleeve in clear colour, has 3.2 mm diameter and 30 cm length with a ratio of 2:1. This very flexible, flame retardant, fluoropolymer clear tubing offers environmental protection where transparency, chemical resistance and high temperatures are required. The tubing sleeve meets NASA SP-R-0022A TML 1.0% CVCN 0.1% pass, SAE-AMS-DTL-23053/13, UL224 VW-1, ESA PSS-01-702 and ASTM E 595 (test method only) standards.

Features and Benefits

- Low shrink temperature +70°C (minimum shrink temperature for full recovery +130°C)
- Highly flexible protection
- Low outgassing
- Fluid resistant
- Fully transparent protection
- Chemical resistant
- Supplied in a bag of 4 at 300 mm cut lengths



Specifications:

Adhesive Lined	No
Angle	Straight
Colour	Clear
Dielectric Strength	30 kV/mm
Flame Retardant	Yes
Halogen Free	No
Material	Fluoropolymer
Maximum Operating Temperature	+200°C
Minimum Operating Temperature	-55°C
Operating Temperature Range	-55 to +200°C
Shrink Ratio	2:1
Shrunk Diameter	1.6 mm
Sleeve Diameter	3.2 mm
Sleeve Length	30 cm
Sleeve Type	Heat Shrink
Standards Met	NASA SP-R-0022A TML 1.0% CVCM 0.1% Pass, SAE-AMS-DTL-23053/13, UL 224 VW-1, ESA PSS-01-702, ASTM E 595, RoHS Compliant