



Type	S.N
J	621-2265
K	621-2271

0	Creation	BLONDEL N.	11.05.2006	DP	11.05.2006
Ind.	Object	Drawn :	Date :	Checked :	Date :
TYPE J / K WASHER E06008-E06009		N°CF TABLE			
		Material :		Scale :	
		-		N.T.S	
		<small>unless otherwise specified Generale tolerances ± 0.1 mm</small>			
				94-05-08-TE-079 Rév.2	

Type	S.N
J	621-2265
K	621-2271

4	Heat shrink	PE
3	Sleeve	PE
2	Cable	FG/S.SBraid
1	Washer	AISI 303
<b>Tag</b>	<b>Description</b>	<b>Material</b>

0	Creation	BLONDEL N.	11.05.2006	DP	11.05.2006
Ind.	Object	Drawn :	Date :	Checked :	Date :

TYPE J / K WASHER E06008-E06009		<b>N° CF Table</b>			
------------------------------------	--	--------------------	--	--	--

	Material : —	Scale : <b>N.T.S</b>
	<small>unless otherwise specified Generale tolerances ± 0.1 mm</small>	 <small>94-05-08-TE-079 R6v.2</small>

**Description**

Washer

**Thermocouple type**

J	621-2265
K	621-2271

**Grounded or Ungrounded**

Grounded

According to IEC-BS 4937 60584-2 & IEC-BS 4937 60584-3

**RoHS compliance**

Yes

**Accuracy Class 2**

±2.5°C or ±0.0075xT

**Colour Codes IEC 60584**

Type	J	K
+VE arm	black	green
-VE arm	white	white
Overall	black	green
T* Range	-50 to +750*	-50 to 1100*
Operating T*	-50 to +400	-50 to +400

**Cable characteristics**

Section	7x0.2
Conductor Insulation	0.22 mm <sup>2</sup>
Braid	Glass fiber
Length	StainlessSteel
	2000 mm

**Washer dimensions**

ø 6mm

**Connection**

Crimped on to wire

**Application**

contact temperature with fixing screw

0	Creation	BLONDEL N	11.05.06	DP	11.05.06
Ind.	Object	Drawn :	Date :	Checked :	Date :

**TYPE J / K WASHER  
E06008 / E06009**

**N° CF TABLE**



Material :

Scale :

N.T.S

Unless otherwise specified generales tolerances ± 0,1mm



94-05-08-TE-079 Rev.2