




Datasheet

MXL Rubber Timing Belts 0.080" (2.032mm) pitch



Rubber back/teeth, glass fibre reinforced, nylon fabric tooth facing to DIN / ISO 5296

RS Stock Number	Width (in.)	Width (mm)	Length (in.)	Length (mm)	No. Teeth
7785039	0.25" (1/4)	6	4.56	115.82	57
7785032	0.25" (1/4)	6	4.80	121.92	60
7785036	0.25" (1/4)	6	5.36	136.14	67
7785045	0.25" (1/4)	6	6.40	162.56	80
7785048	0.25" (1/4)	6	6.80	172.72	85
7785042	0.25" (1/4)	6	7.20	182.88	90
7785051	0.25" (1/4)	6	7.52	191.01	94
7785054	0.25" (1/4)	6	7.60	193.04	95
7785058	0.25" (1/4)	6	8.00	203.20	100
7785067	0.25" (1/4)	6	8.24	209.30	103
7785060	0.25" (1/4)	6	8.40	213.36	105
7785064	0.25" (1/4)	6	9.12	231.65	114
7785073	0.25" (1/4)	6	9.20	233.68	115
7785076	0.25" (1/4)	6	10.08	256.03	126
7785070	0.25" (1/4)	6	10.40	264.16	130
7785089	0.25" (1/4)	6	12.00	304.80	150
7785082	0.25" (1/4)	6	12.80	325.12	160
7785086	0.25" (1/4)	6	13.20	335.28	165
7785095	0.25" (1/4)	6	15.20	386.08	190



ENGLISH

7785098	0.25" (1/4)	6	16.00	406.40	200
7785092	0.25" (1/4)	6	20.48	520.19	256
7785102	0.25" (1/4)	6	25.20	640.08	315

RS, Professionally Approved Products, gives you professional quality parts across all products categories. Our range has been testified by engineers as giving comparable quality to that of the leading brands without paying a premium price.