

FEATURES

- Vertical mounting with 3-pole
- Stereo Socket for high accuracy
- 3.5 mm size
- Versatile Connector for many audio applications
- 30 m Ω maximum Contact Resistance
- Insulation Resistance of 100M Ω minimum at 500 V DV
- Dielectric Withstand Voltage of 500V ac for 1 minute

RS PRO 3.5 mm Panel Mount Stereo Jack Socket, 3Pole

RS Stock No.: 907-5680



RS Professionally Approved Products bring to you professional quality parts across all product categories. Our product range has been tested by engineers and provides a comparable quality to the leading brands without paying a premium price.

Product Description

Even though 3.5 mm Jack Socket exists on the market for a while, it is still reliable Socket ensuring clean contact surfaces with each operation. The 3.5 mm Jack Connector, known as a mini-jack plug or mini-jack Socket is suitable for less demanding applications, but durable nylon panel mount is getting you excellent performance. The PCB (printed circuit board) mount is ideal for portable devices, such as iPods, tablets or cable headphones.

General Specifications

Type	Stereo
Gender	Female
Mounting Type	Panel Mount
Contact Plating	Silver
Colour	Black
Contact Material	PBT
No of Poles/Way	3
Application	MP3 Players, Hi-fi systems, Games-Consoles, mobile phones

Electrical Specifications

Voltage Rating	500 V ac, 500 V dc
Current Rating	1A
Contact resistance	30mΩ max
Insulation resistance	100M Ω min. @ DC 500V
Withstand voltage	AC 500V for 1 minute

Mechanical Specifications

Size	3.5 mm
Body Orientation	Vertical
Termination Method	Solder

Approvals

Compliance/Certifications	2011/65/EU and 2015/863
---------------------------	-------------------------

