

UIA&UIB Series

AC/DC Adaptor **45W** Series Desktop




▲ **UIA345**



▲ **UIB345**



■ Please contact our sales department for safety standard of each model.



Product Highlights

- Stability
- Compact size
- Energy efficiency
- Suit LCD display, hand held computer, multimedia player etc.

Efficiency

- Meet Coc V Tier2

Immunity

- EN55024/A1:2001

Protection

- Short circuit protection
- Over Voltage Protection
- Over Current Protection
- Over Temperature Protection

Emissions

- FCC Part15 Class B
- CE CISPR 32 Class B
- VCCI Class B
- GB9254/GB17625.1
- KN32 KN35
- AS/NZS CISPR32
- TP TC 020/2011

Safety Approvals

- UL60950
- CAN/CSA C22.2 NO. 60950
- PSE
- IEC/EN60950-1
- GB4943.1
- K60950
- AS/NZS 60950.1
- TP TC 004/2011

Input					
Description	Min	Typ	Max	Units	Comment
Voltage	90	100~240	264	VAC	
Frequency	47	50/60	63	Hz	

Environmental					
Description	Min	Typ	Max	Units	Comment
Operating Temperature	0	-	40	°C	Free Convection,Sea level
Storage Temperature	-20	-	65	°C	Free Convection,Sea level
Operating Humidity	5	-	95	%RH	No Condensing
Storage Humidity	5	-	95	%RH	No Condensing

Typical model list

Input Condition		DC Output Voltage	DC Output Current	Output Voltage Precision	Ripple	Noises	Regulation		Option/Remark
							Line	Load	
Input Voltage: 90V-264Vac Frequency: 47-63Hz	1	12V	3.8A	±5%	300mV	300mV	2%	10%	
	2	14V	3.21A	±5%	200mV	200mV	2%	10%	
	3	15V	3.0A	±5%	200mV	200mV	2%	10%	
	4	16V	2.8A	±5%	200mV	200mV	2%	10%	
	5	19V	2.4A	±5%	300mV	300mV	2%	10%	
	6	24V	1.9A	±5%	200mV	200mV	2%	10%	
	7	35V	1.3A	±5%	200mV	200mV	2%	10%	
	8	48V	0.9A	±5%	300mV	300mV	2%	10%	
	9	-	-	-	-	-	-	-	

■ Measurement condition

1. Measurements shall be made with an oscilloscope with 20MHz bandwidth.

2. Outputs shall be bypassed at the connector with a 0.1uF ceramic disk capacitor and a 10uF electrolytic capacitor to simulate system loading.

Mechanical Spec

UIA Series	UIT Series

■ Please contact our sales department for details of each model ■