



CONTACT & WIRE ASSEMBLY


1. ANODE CONTACT & WIRE COMBINATION  
MATERIAL: BRASS NICKEL PLATED



2. CATHODE CONTACT & WIRE COMBINATION  
MATERIAL: PHOSPHOR BRONZE NICKEL PLATED



3. ANODE CATHODE: SPRING STEEL NICKEL PLATED



SPECIFICATION

- (1) ITEM NO. : BHC-331A150MM
- (2) WIRE: UL1007 AWG #26  
BLACK & RED: 150MM±5MM  
STRIP & TIN: 5MM±1MM
- (3) HOLDER MATERIAL: PP UL94HB RESIN, BLACK COLOR
- (4) CONTACT MATERIAL:  
ANODE: 0.25MM THICK BRASS NICKEL PLATED  
CATHODE: 0.25MM THICK PHOSPHOR BRONZE NICKEL PLATED  
ANODE CATHODE: 0.20MM THICK SPRING STEEL NICKEL PLATED
- (5) RoHS COMPLIANT

3						
2						
1			NAME	BATTERY HOLDER: BHC-331A150MM		
NO.	MODIFICATION	DATE	SCALE	1:1	APPD	游原正
General Tolerances			UNIT	MM	CHKD	黄永连
0 ~ >3	± 0.10	30 ~ >120	MAT'L	SEE SPEC.	DWN	RAOXIANHUI
3 ~ >6	± 0.10	120 ~ >400	DATE	NOV. 10. 2014	DR NO	331A-1114
6 ~ >30	± 0.20	Angle: ± 3°	The Third Angle Projection			