



CONTACT & WIRE ASSEMBLY


1. ANODE CONTACT & WIRE COMBINATION  
MATERIAL: BRASS NICKEL PLATED




2. CATHODE CONTACT & WIRE COMBINATION  
MATERIAL: PHOSPHOR BRONZE NICKEL PLATED



3. ANODE CATHODE: SPRING STEEL NICKEL PLATED



4. CATHODE ANODE: SPRING STEEL NICKEL PLATED



SPECIFICATION

- (1) ITEM NO. : BHC-341A150MM
- (2) WIRE: UL1007 AWG #26  
BLACK & RED: 150MM±5MM  
STRIP & TIN: 5MM±1MM
- (3) HOLDER MATERIAL: PP UL94HB RESIN, BLACK COLOR
- (4) CONTACT MATERIAL:  
ANODE: 0.25MM THICK BRASS NICKEL PLATED  
CATHODE: 0.25MM THICK PHOSPHOR BRONZE NICKEL PLATED  
ANODE CATHODE: 0.20MM THICK SPRING STEEL NICKEL PLATED  
CATHODE ANODE: 0.20MM THICK SPRING STEEL NICKEL PLATED
- (5) RoHS COMPLIANT

3							
2							
1							
NO.	MODIFICATION	DATE	NAME	BATTERY HOLDER: BHC-341A150MM			
			SCALE	1:1	APPD	游原正	
General Tolerances			UNIT	MM	CHKD	黄永连	
0 ~ >3	± 0.10	30 ~ >120	MAT'L	SEE SPEC.	DWN	RAOXIANHUI	
3 ~ >6	± 0.10	120 ~ >400	DATE	NOV. 10. 2014	DR NO	341A-1114	
6 ~ >30	± 0.20	Angle: ± 3°	The Third Angle Projection				