


Characters

- § High intensity.
- § Viewing angle 15°.
- § Reliable and Rugged
- § Standard 3mm diameter package.

ITEM	MATERIALS
Resin(Mold)	Epoxy
Lens Color	Water Transparent
Lead Frame	Ag Plating Iron Alloy
Dice	AlInGaP/GaAs


Outline Dimensions



Absolute Maximum Ratings (Ta=25°C)

Item	Symbol	Value	Unit
		Red	
Power Dissipation	PD	80	mW
DC Forward Current	IF	20	mA
Pulsed Forward Current	IFP	100 *	mA
Reverse Voltage	VR	5 ▲	V
Operating Temperature	Topr	-25 ~ +80	°C
Storage Temperature	Tstg	-40 ~ +100	°C
Soldering Temperature△	Tsol	260	°C

Directive Characteristics (Ta=25°C)



* Duty 1/10 Pulse Width 0.1ms This Rating is Zener Diode

At the position of 4mm from the bottom of the package within 5 seconds.

Electrical-Optical Characteristics (Ta=25°C)

Part No.	Luminous Intensity (mcd) ☆			Forward Voltage (V)			Forward Voltage (V)		Reverse Current (μA)		Wavelength Characteristics (nm)			
	Typ.	Min.	IF (mA)	Typ.	Max.	IF (mA)	Min.	IF (μA)	Max.	VR (V)	λ D Typ.	λ D Max.	Δ λ Typ.	IF (mA)
BL304V2CA2A01	700	538	20	1.8	2.4	20	1.3	100	50	5	630	635◆	20	20

☆ Axial Direction (luminous Intensity)

◆ Products are sorted by wavelength, which cannot be specified by customer..

Notes:


- § All dimensions are in millimeters (inches) .
- § Tolerance is ± 0.25 (.010) mm unless otherwise noted.
- § Protruded resin under flange is 1.0 mm (.04) max.
- § Lead spacing is measured where the leads emerge from the package.

Relative Luminous Intensity


Typical Characteristics

The data typical , and the value is not guaranteed.


IF-VF($T_a=25^{\circ}\text{C}$)




Relative Luminous Intensity-IF
($T_a=25^{\circ}\text{C}$)




Wavelength Characteristics
($T_a=25^{\circ}\text{C}$)




Relative Luminous Intensity-Ta



IF-Ta



$\theta - \lambda$ ($T_a=25^{\circ}\text{C}$)



Wavelength λ (nm)