Screwless - the reliable connection!

Screwless clamp technology drastically reduces wiring time, eliminates routine maintenance, and ensures a very reliable connection. That's why Omron now introduces a new range of screwless I/O units for the CJ1 PLC series.



Omron's screwless I/O terminals accept a wide range of wires, solid or stranded, with or without ferrules, from 0.08 to 1.5 mm². The common power supply terminals even accept two wires each, for easier power distribution.

Because the spring-loaded clamps secure the wires in their sockets, the wiring will not come loose through shock or vibration. This eliminates the routine task of re-tightening screws during regular inspection. During testing and commissioning, the spring clamps can be contacted to verify the signal levels. Yet the terminal is always safe to touch, whether wires are inserted or not.

Easy to use

Individual wires are easy to attach and detach from the terminal block, simply by inserting a screwdriver in the release hole. Traditional screw terminals must be tightened at the correct torque; with Omron's screwless I/O, the contact pressure is always right. A special insert in our clamping spring protects it from being over-stressed, making sure the spring always stays in shape.

Advanced Industrial Automation

Designed and manufactured in Europe according to Omron's high quality standards, the CJ1 screwless I/O units are an ideal alternative for panel makers and machine builders who want to reduce installation time and add an extra dimension in secure, reliable connections for all their control wiring.

The new screwless I/O terminal is interchangeable with existing connectors, and can be used on any existing CJ1 unit that uses the classic 18-point screw terminal block. And they are just as convenient to attach or detach; no tools required!



Connecting wires to conventional screw terminals requires a lot of work. See why it makes sense to use Omron screwless I/O units for all your I/O!





The new CJ1 screwless I/O terminal block is supplied with the following units				
Model	Туре	Specification		
CJ1W-ID211 (SL)	16 DC inputs	24V DC, 7mA		
CJ1W-0C201 (SL)	8 relay outputs	250V AC, 2A, (max. 16A total)		
CJ1W-0C211 (SL)	16 relay outputs	250V AC, 2A, (max. 8A total, one common)		
CJ1W-OD211 (SL)	16 transistor outputs (sink)	12-24V DC, 0.5A, (max. 5A total, one common)		
CJ1W-OD212 (SL)	16 transistor outputs (source)	24V DC, 0.5A, (max. 5A total, one common)		
CJ1W-AD041-V1 (SL)	4 analogue inputs	1 to 5V, 0 to 10V, 0 to 5V, -10 to 10V, 4 to 20mA		
CJ1W-AD081-V1 (SL)	8 analogue inputs	1 to 5V, 0 to 10V, 0 to 5V, -10 to 10V, 4 to 20mA		
CJ1W-DA021 (SL)	2 analogue outputs	1 to 5V, 0 to 10V, 0 to 5V, -10 to 10V, 4 to 20mA		
CJ1W-DA041 (SL)	4 analogue outputs	1 to 5V, 0 to 10V, 0 to 5V, -10 to 10V, 4 to 20mA		
CJ1W-DA08C (SL)	8 analogue outputs (current)	4 to 20mA		
CJ1W-DA08V (SL)	8 analogue outputs (voltage)	1 to 5V, 0 to 10V, 0 to 5V, -10 to 10V		
CJ1W-MAD42 (SL)	4 analogue outputs + 2 analogue outputs	1 to 5V, 0 to 10V, 0 to 5V, -10 to 10V, 4 to 20mA		
CJ1W-TS561 (SL)	6 thermocouple inputs	Type J / Type K selectable		
CJ1W-TS562 (SL)	6 RTD inputs	Pt100 / Pt1000 selectable		

Omron's CJ1 screwless I/O features at a glance:

- Drastically reduces wiring time
- Accepts a wide range of wiring gauges
- Easy to attach and detach; no tools required
- Easy to test signals, even while wiring is connected
- Construction prevents overstressing of clamping spring
- Interchangeable with existing CJ1 screw terminals
- Safe no metal parts can be touched by fingers

Spare screwless terminal blocks
CJ-WM01-18P-5
Set of 5 screwless terminal blocks
Suitable for all CJ1 I/O units with 18-point
terminals blocks (except thermocouple
units with external cold-junction
compensation sensor, e.g. CJ1W-TC00_)

INDEPENDENT DISTRIBUTOR SALES **Omron Electronics B.V.** Wegalaan 61, 2132 JD Hoofddorp The Netherlands Tel: +31 (0) 23 568 13 00 Fax: +31 (0) 23 568 13 97 www.europe.omron.com

OMRON

For further information please contact OMRON on one of the following, or complete and fax back the form.

□ Please send me further information on the CJ1 PLC series.	General telephone enquiries Direct e-mail address for sales	: +31 (0) 23 568 13 00 enquiries : ids@eu.omron.com
□ Please call to discuss the CJ1 Screwless I/O.	OMRON website	: www.europe.omron.com
Name		Position
Company		
Address		
Post Code	Tel	Fax
E-mail	Industry	
Fax this to OMPON on +31 (0) 23 568 13 97		Although we strive for perfection, Omron Europe BV and/or its subsidiary and affiliated companie do not warrant or make any representations regarding the correctness or completeness of th