

Jul.1.2018 Copyright 2018 HIROSE ELECTRIC CO., LTD. All Rights Reserved.  
 In case that the application demands a high level of reliability, such as automotive,  
 please contact a company representative for further information.

COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE	COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE	
△					△					
△					△					
<b>APPLICABLE STANDARD</b>										
<b>RATING</b>	OPERATING TEMPERATURE RANGE	-35 °C TO 85 °C(NOTE 1)			STORAGE TEMPERATURE RANGE	-10°C TO 60 °C				
	VOLTAGE	250 V AC			APPLICABLE CONNECTORS	DF1B(A) — * (D): EP-2.5RC				
	CURRENT	AWG22~20 : 3A			OPERATING HUMIDITY RANGE	UL1007,1061:AWG22~20				
<b>SPECIFICATIONS</b>										
<b>ITEM</b>		<b>TEST METHOD</b>			<b>REQUIREMENTS</b>			<b>QT</b>	<b>AT</b>	
<b>CONSTRUCTION</b>										
GENERAL EXAMINATION		VISUALLY AND BY MEASURING INSTRUMENT			ACCORDING TO DRAWING			X	X	
MARKING		CONFIRMED VISUALLY.						X	X	
<b>ELECTRIC CHARACTERISTICS</b>										
CONTACT RESISTANCE		100 mA (DC OR 1000 Hz).			30 mΩ MAX.			X	—	
CONTACT RESISTANCE MILLIVOLT LEVEL METHOD		20 mV MAX. mA(DC OR 1000 Hz).			mΩ MAX.			—	—	
INSULATION RESISTANCE		500 V DC.			MΩ MIN.			—	—	
VOLTAGE PROOF		650 V AC FOR 1 min.			NO FLASH OVER OR BREAKDOWN.			—	—	
<b>MECHANICAL CHARACTERISTICS</b>										
CONTACT INSERTION AND EXTRACTION FORCES		BY STEEL GAUGE.			INSERTION FORCE		N MAX.		—	
					EXTRACTION FORCE		N MIN.		—	
INSERTION AND WITHDRAWAL FORCES		MEASURED BY APPLICABLE CONNECTOR.			INSERTION FORCE		N MAX.		—	
					EXTRACTION FORCE		N MIN.		—	
MECHANICAL OPERATION		30 TIMES INSERTIONS AND EXTRACTIONS			① CONTACT RESISTANCE: 30 mΩ MAX.		② NO DAMAGE, CRACK AND LOOSENESS OF PARTS.		X	
VIBRATION		FREQUENCY 10 TO 55 Hz. SINGLE AMPLITUDE 0.75mm. — m/s <sup>2</sup> AT 2 h, FOR 3 DIRECTIONS.			① NO ELECTRICAL DISCONTINUITY OF 1μs.		② CONTACT RESISTANCE: 30 mΩ MAX.		X	
SHOCK		490 m/s <sup>2</sup> DIRECTIONS OF PULSE 11 ms AT 3 TIME FOR 3 DIRECTION.			③ NO DAMAGE, CRACK AND LOOSENESS OF PARTS.				X	
<b>ENVIRONMENTAL CHARACTERISTICS</b>										
RAPID CHANGE OF TEMPERATURE		TEMPERATURE -55 → -5 TO 35 → 85 → 5 TO 35 °C TIME 30 → 10 → 30 → 10 min UNDER 5 CYCLES.			① CONTACT RESISTANCE: 30 mΩ MAX.		② INSULATION RESISTANCE: 1000MΩ MIN.		③ NO DAMAGE, CRACK AND LOOSENESS OF PARTS.	
DAMP HEAT (STEADY STATE)		EXPOSED AT 40±2 °C, 90 TO 95 %, 96 h.			① CONTACT RESISTANCE: 30 mΩ MAX.		② INSULATION RESISTANCE: — MΩ MIN.		③ NO DAMAGE, CRACK AND LOOSENESS OF PARTS.	
CORROSION SALT MIST		EXPOSED IN — % SALT WATER SPRAY FOR h.			① CONTACT RESISTANCE: mΩ MAX.		② NO HAEAVY CORROSION.		—	
HYDROGEN SULPHIDE		EXPOSED IN — PPM FOR — h. (TEST STANDARD: JEIDA-38)			① CONTACT RESISTANCE: mΩ MAX.		② NO HAEAVY CORROSION.		—	
SULPHUR DIOXIDE		EXPOSED IN — PPM FOR — h. (TEST STANDARD: JEIDA-39)			① CONTACT RESISTANCE: mΩ MAX.		② NO HAEAVY CORROSION.		—	
SOLDERING HEAT		SOLDER TEMPERATURE, °C FOR IMMERSION, DURATION, S			NO DEFORMATION ON CASE OR EXCESSIVE LOOSENESS OF THE TERMINALS					
SOLDERABILITY		SOLDERED AT SOLDER TEMPERATURE, °C FOR IMMERSION DURATION, S.			SOLDER SHALL COVER MINIMUM OF 95 % OF THE SURFACE BEING IMMERSED					
<b>REMARKS</b>				<b>DRAWN</b>	<b>DESIGNED</b>	<b>CHECKED</b>	<b>APPROVED</b>	<b>RELEASED</b>		
NOTE1: INCLUDE THE TEMPERATURE RISING BY CURRENT				W. Fukuchi	W. Fukuchi	C. Harami	K. Katayama			
Unless otherwise specified, refer to MIL-STD-1344.				'99.11.12	'99.11.12	'99.11.12	'99.11.12			
Note QT: Qualification Test AT: Assurance Test X: Applicable Test										
<b>HRS HIROSE ELECTRIC CO., LTD.</b>				<b>SPECIFICATION SHEET</b>			<b>PART NO.</b>			
							<b>DF1B-2022PC</b>			
CODE NO (CLD)			DRAWING NO.			PART NO.			1	
CL			ELC4-020432			CL541-0260-8			/	

TO

