

COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE	COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE
△				.	△				.
△				.	△				.

APPLICABLE STANDARD				
RATING	OPERATING TEMPERATURE RANGE	-35 ℃ TO +85 ℃ (NOTE1)	STORAGE TEMPERATURE RANGE	-10 ℃ TO +60 ℃
	VOLTAGE	250 V AC	APPLICABLE CONTACT	
	CURRENT	3 A	APPLICABLE CONNECTOR	
			APPLICABLE CABLE	

SPECIFICATIONS

ITEM	TEST METHOD	REQUIREMENTS	Q	T	A	T
CONSTRUCTION						
GENERAL EXAMINATION	VISUALLY AND BY MEASURING INSTRUMENT.	ACCORDING TO DRAWING.				
MARKING	CONFIRMED VISUALLY.					
ELECTRICAL CHARACTERISTICS						
CONTACT RESISTANCE	100 mA (DC OR 1000 Hz).	30 mΩ MAX.				
CONTACT RESISTANCE MILLIVOLT LEVEL METHOD.	20 mV MAX. mA (DC OR 1000 Hz).	mΩ MAX.				
INSULATION RESISTANCE	500 V DC	1000 MΩ MIN.				
VOLTAGE PROOF	650 V AC FOR 1 min	NO FLASHOVER OR BREAKDOWN.				
MECHANICAL CHARACTERISTICS						
CONTACT INSERTION AND EXTRACTION FORCES	BY STEEL GAUGE.	INSERTION FORCE N MAX. EXTRACTION FORCE N MIN.				
INSERTION AND WITHDRAWAL FORCES	MEASURED BY APPLICABLE CONNECTOR.	INSERTION FORCE N MAX. EXTRACTION FORCE N MIN.				
MECHANICAL OPERATION	30 TIMES INSERTIONS AND EXTRACTIONS	① CONTACT RESISTANCE: 30 mΩ MAX. ② NO DAMAGE, CRACK AND LOOSENESS OF PARTS.				
VIBRATION	FREQUENCY 10 TO 55 Hz. SINGLE AMPLITUDE 0.75 mm. m/s ² AT 2 h FOR 3 DIRECTIONS.	① NO ELECTRICAL DISCONTINUITY OF PARTS. ② CONTACT RESISTANCE: — mΩ MAX. ③ NO DAMAGE, CRACK AND LOOSENESS OF PARTS.				
SHOCK	490 m/s ² DURATION OF PULSE 11 ms AT 3 TIMES FOR 3 DIRECTIONS.	① NO ELECTRICAL DISCONTINUITY OF PARTS. ② CONTACT RESISTANCE: — mΩ MAX. ③ NO DAMAGE, CRACK AND LOOSENESS OF PARTS.				
ENVIRONMENTAL CHARACTERISTICS						
DAMP HEAT (STEADY STATE)	EXPOSED AT 40±2 ℃, 90~95%, 96 h.	① CONTACT RESISTANCE: 30 mΩ MAX. ② INSULATION RESISTANCE: 1000 MΩ MIN. ③ NO DAMAGE, CRACK AND LOOSENESS OF PARTS.				
RAPID CHANGE OF TEMPERATURE	TEMPERATURE -55 → -5~35 → +85 → 5~35 ℃ TIME 30 → 5 → 30 → 5 min UNDER 5 CYCLES.	① CONTACT RESISTANCE: 30 mΩ MAX. ② INSULATION RESISTANCE: 1000 MΩ. ③ NO DAMAGE, CRACK AND LOOSENESS OF PARTS.				
RESISTANCE TO SOLDERING HEAT	SOLDER TEMPERATURE, ℃ FOR IMMERSION, DURATION, s.	NO DEFORMATION OF CASE OF EXCESSIVE LOOSENESS OF THE TERMINALS.				
SOLDERABILITY	SOLDERED AT SOLDER TEMPERATURE, ℃ FOR IMMERSION DURATION, s.	A NEW UNIFORM COATING OF SOLDER SHALL COVER A MINIMUM OF 95 % OF THE SURFACE BEING IMMersed.				
REMARKS		DRAWN	DESIGNED	CHECKED	APPROVED	RELEASED
NOTE1 INCLUDE THE TEMPERATURE RISING BY CURRENT.		R. Sasaki	M. Tanaka	J. Oma	H. Yamamoto	
Unless otherwise specified, refer to MIL-STD-1344.		'95.10.12	'95.10.13	'95.10.17	'95.10.23	
Note Q: Qualification Test A: Assurance Test O: Applicable Test						
HRS HIROSE ELECTRIC CO., LTD.		SPECIFICATION SHEET		PART NO.		
CODE NO. (OLD)		DRAWING NO.		CODE NO.		
CL		ELC4-160595		CL		
CODE NO. SHALL BE IN ACCORDANCE WITH TABLE.						

TO