
■Crimping Contact for Socket



Part Number	CL No.	Туре	Quantity		Finish
DF3-22SCF	543-0235-3	Reel contact	10000 pcs.	per embossed tape bag	
DF3-22SC	543-0236-6	Bulk contact	100 pcs.	per embossed tape bag	Tip plated
DF3-2428SCF	543-0001-2	Reel contact	10000 pcs.	per embossed tape bag	Tin plated
DF3-2428SC	543-0002-5	Bulk contact	100 pcs.	per embossed tape bag	
DF3-2428SCFC	543-0046-0	Reel contact	10000 pcs.	per embossed tape bag	Cold plated
DF3-248SCC	543-0047-3	Bulk contact	100 pcs.	per embossed tape bag	Gold plated

Applicable Wire (Tin Plating Annealed **Copper Wire)**

Conductor Size (Wire Configuration)	Jacket Diameter
AWG 22 (17pcs./0.16mm)	<i>ϕ</i> 1.2 to <i>ϕ</i> 1.45mm
AWG 24 (11pcs./0.16mm)	
AWG 26 (7pcs./0.16mm)	<i>∮</i> 0.75 to <i>∮</i> 1.45mm
AWG 28 (7pcs./0.127mm)	

Recommended Wire


UL1061, UL1007 (Note 2.)

Strip Length

1.8 to 2.3mm

Note1: If other wires are used instead of the applicable cable, please contact HRS company. Note2: DF3-22SCF is applicable to UL1061.

■Crimping Contact for In-line Plug



Part Number	CL No.	Туре	Quantity		Finish
DF3-EP2428PCF	543-0062-7	Reel contact	10000 pcs.	per reel	.
DF3-EP2428PC	543-0063-0	Bulk contact	100 pcs.	per pack	Tin plated
DF3-EP2428PCFA	543-0149-3	Reel contact	10000 pcs.	per reel	
DF3-EP2428PCA	543-0150-2	Bulk contact	100 pcs.	per pack	Gold plated

Applicable Wire (Tin Plating Annealed Copper Wire)

Conductor Size (Wire Configuration)	Jacket Diameter
AWG 24 (11pcs./0.16mm)	
AWG 26 (7pcs./0.16mm)	<i>ϕ</i> 0.75 to <i>ϕ</i> 1.45mm
AWG 28 (7pcs./0.127mm)	

Recommended Wire

UL1061, UL1007

Strip Length

1.9 to 2.5mm

Note1: If other wires are used instead of the applicable cable, please contact HRS company.

◆Applicable Crimping Tool

Туре	Part Number	CL No.	Applicable Contact
Applicator	AP105-DF3-2428S	901-4503-3	DF3-2428SCF/SCFC
	AP105-DF3-22S	901-4549-4	DF3-22SCF
	AP105-DF3-EP2428P	901-4508-7	DF3-EP2428PCF/PCFA
Press Unit	CM-105	901-0005-4	
Hand Crimping Tool	DF3-TA2428HC	550-0164-5	DF3-2428SC/SCC
	DF3EP-TA2428HC	550-0184-2	DF3-EP2428PC/PCA
	DF3-TA22HC	550-0257-4	DF3-22SC
Extraction Tool	DE C DO (A)	FF0 0170 9	DF3-***SCF
EXITACTION 1001	DF-C-PO (A)	550-0170-8	DF3-EP***PCF

Note: If any trouble has occurred due to tools other than designated tool, Hirose bears no respoisibility for any trouble.