

Applicable standard						
Rating	Operating temperature range	-30°C to + 85°C(Note 1)		Storage temperature range	-10°C to + 60°C	
	Voltage	250V AC		UL・CSA Rating 	30V AC	
	Current	AWG 24 : 3A AWG 26 : 2A AWG 28 : 1A			AWG 24 : 3A AWG 26 : 2A AWG 28 : 1A	
	Applicable contact	DF3-EP2428PCF (A) DF3-EP2428PC (A)		Applicable connector	DF3-*S-2C	
			Applicable cable	UL1061, 1007 AWG24 to 28		
Specifications						
Item		Test method		Requirements	QTAT	
Construction						
General examination		Visually and by measuring instrument.		According to drawing.	X	X
Marking		Confirmed visually.			X	X
Electric characteristics						
Insulation resistance		500V DC.		1000MΩ MIN.	X	—
Voltage proof		650V AC for 1 min.		No flashover or breakdown.	X	—
Mechanical characteristics						
Vibration		Frequency 10 to 55 Hz, single amplitude 0.75 mm, at 2 h, for 3 directions.		① No electrical discontinuity of 1μs.	X	—
Shock		490 m/s ² duration of pulse 11 ms at 3 times for 3 directions.		② No damage, crack or looseness of parts.	X	—
Environmental characteristics						
Rapid change of temperature		Temperature -55→ 5 to 35→+85→ 5 to 35 °c Time 30→ 5 to 15 → 30→ 5 to 15 min Under 5 cycles.		① Insulation resistance: 1000MΩ MIN. ② No damage, crack or looseness of parts.	X	—
Damp heat (Steady state)		Exposed at 40 ± 2 °c, 90 to 95 %, 96 h.		① Insulation resistance: 1000MΩ MIN. ② No damage, crack or looseness of parts.	X	—
	count	description of revisions		designed	checked	date
	1	DIS-H-00001155		MI. SAKIMURA	TS. FUKUSHIMA	15. 12. 04
Remarks Note 1:Including the temperature rise by current. Unless otherwise specified , refer to IEC 60512.				Approved	KJ. KATAYOSE	05. 01. 05
				Checked	KI. AKIYAMA	05. 01. 05
				Designed	TH. ARAI	05. 01. 05
				Drawn	TH. ARAI	05. 01. 05
Note QT:Qualification Test AT:Assurance Test X:Applicable Test				Drawing no.		ELC-162330-00-01
	Specification sheet			Part no.	DF3-*EP-2C	
	Hirose electric co., ltd.			Code no.	CL543	 1/1