



4	高効率電動機搭載 EQUIPPED WITH HIGHLY EFFECTIVE ELECTRIC MOTOR	
3	吸込・吐出 金網付 (4メッシュ d0.7) WITH SUCTION AND DISCHARGE WIRE NET (4 MESH d0.7)	
2	保護方式 ENCLOSURE	全閉外扇形 TOTALLY ENCLOSED FAN COOLED TYPE
	出力 OUTPUT (kW)	0.4
2	極数・相 POLES PHASE	2・3
	周波数 FREQUENCY (Hz)	50 60
2	電圧 VOLTAGE (V)	200 200/220
	IEコード又は効率基準 IE CODE OR EFFICIENCY STANDARD	76.0% 77.0%
1	風量 (MAX.) VOLUME (m ³ /min)	15 16
	静圧 (MAX.) [kPa] STATIC PRESSURE	0.70 1.00
1	回転数 SPEED (min ⁻¹)	2900 3450
	標準吸込状態 STANDARD SUCTION CONDITION	温度 TEMPERATURE 20℃ 相対湿度 HUMIDITY 65% 絶対圧力 ABSOLUTE P. 101.3 kPa
仕様 SPECIFICATIONS		

作成 DRAW	T. TAKAYAMA	作成日 DATE	2013. 5. 24 MAY 24, 2013
確認 CONFIRM	Y. FUJITA	品名 TYPE	FSM-H04-R313
承認 APPROVE	S. HATANO	図名 TITLE	外形寸法図 EXTERNAL DIMENSIONS
昭和電機株式会社 大東工場 SHOWA DENKI CO., LTD DAITO FACTORY		図番 DRAWING NO.	YB13R31301-0

修正	△×			
	△×			
	△×			
図歴 RECORDS		変更日 DATE	変更内容 REVISION	変更 REVISED BY