

APPLICABLE STANDARD					
RATING	OPERATING TEMPERATURE RANGE	-30 °C TO 60 °C ⁽¹⁾	APPLICABLE CABLE (OUTER DIAMETER)	20contacts	φ 1.7mm MAX
	STORAGE TEMPERATURE RANGE	-10 °C TO 60 °C ⁽²⁾		26~40contacts	φ 1.6mm MAX
	OPERATING HUMIDITY RANGE	40 % TO 80 %		50,60contacts	φ 1.4mm MAX
	STORAGE HUMIDITY RANGE	40 % TO 70 % ⁽²⁾			
SPECIFICATIONS					
ITEM	TEST METHOD	REQUIREMENTS	QT	AT	
CONSTRUCTION					
GENERAL EXAMINATION	VISUALLY AND BY MEASURING INSTRUMENT.	ACCORDING TO DRAWING.	x	x	
MARKING	CONFIRMED VISUALLY.		x	x	
	COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
△					
REMARK ⁽¹⁾ TEMPERATURE RISE INCLUDED WHEN ENERGIZED. ⁽²⁾ THIS STORAGE INDICATES A LONG-TERM STORAGE STATE FOR THE UNUSED PRODUCT BEFORE THE BOARD MOUNTED.			APPROVED	HS. OKAWA	12. 09. 11
			CHECKED	HT. YAMAGUCHI	12. 09. 11
			DESIGNED	KJ. NISHIWAKI	12. 09. 11
			DRAWN	CR. TAKESHIMA	12. 09. 11
Note QT:Qualification Test AT:Assurance Test X:Applicable Test			DRAWING NO.		ELC4-016704-72
HRS	SPECIFICATION SHEET		PART NO.	HIF3-34CV (72)	
	HIROSE ELECTRIC CO., LTD.		CODE NO.	CL562-0204-8-72	△ 1/1