




APPLICABLE STANDARD					
RATING	OPERATING TEMPERATURE RANGE	-30 °C TO 60 °C ⁽¹⁾	OPERATING HUMIDITY RANGE	40 % TO 80 %	
	STORAGE TEMPERATURE RANGE	-10 °C TO 60 °C ⁽²⁾	STORAGE HUMIDITY RANGE	40 % TO 70 % ⁽²⁾	
			APPLICABLE CABLE (OUTER DIAMETER)	φ 1.4mm MAX	
SPECIFICATIONS					
ITEM	TEST METHOD	REQUIREMENTS	QT	AT	
CONSTRUCTION					
GENERAL EXAMINATION	VISUALLY AND BY MEASURING INSTRUMENT.	ACCORDING TO DRAWING.	x	x	
MARKING	CONFIRMED VISUALLY.		x	x	
	COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
					
REMARK ⁽¹⁾ TEMPERATURE RISE INCLUDED WHEN ENERGIZED. ⁽²⁾ THIS STORAGE INDICATES A LONG-TERM STORAGE STATE FOR THE UNUSED PRODUCT BEFORE THE BOARD MOUNTED.			APPROVED	HS. OKAWA	12. 01. 16
			CHECKED	HT. YAMAGUCHI	12. 01. 16
			DESIGNED	YJ. ASAO	12. 01. 16
			DRAWN	YJ. ASAO	12. 01. 16
Note QT:Qualification Test AT:Assurance Test X:Applicable Test			DRAWING NO.	ELC4-016706-22	
	SPECIFICATION SHEET		PART NO.	HIF3-50CV (72)	
	HIROSE ELECTRIC CO., LTD.		CODE NO.	CL562-0206-3-72	 1/1