ROBO サドル

裸圧着端子

裸圧着 スリーブ

リング スリーブ

絶縁被覆付 圧着接続子

電線コネクタ

サドル

ケーブル 支持材

ケーブル しばりひも

バインド線

カラー ワイヤー

モール

Nダクト

マーカー用 絶縁チューブ

線名札

結束バンド

支持材

ケーブル 引込保護材


プルボックス

埋設標示シート

## 裸圧着端子 丸形(R形) 1.25~8









■ 仕 様● 材質:無酸素銅

US LR20812 JQ0608019 / JQID08002 / JQMY14001 / JIS C 2805

ISTED L42024 WELITZO	42024 <b>⑤</b> LR20812 ⑤ JQ0608019 / JQID08002 / JQMY14001 / JIS C 2805 寸法 (mm) 安田馬伯笠田 標準 堀点 出													
商品コード	品番	規格	ød <sub>2</sub>	В	L					Т	適用電線範囲	標準単価	梱包	出荷 単位
690-350-01100	R 1.25-3 JP	<u>®</u> <b>©</b> 00			11.5	4.0				-				—
690-350-01110		(h) (g)	3.7 3.7 4.3	5.5	13.2	5.6	4.8				単線:0.57〜1.44mm より線:0.25〜1.65mi AWG:#22〜#16		1,000個(10箱)	100個(1箱)
690-350-01120	1.25-3.7 JP	(h) (h		5.5	11.5	4.0		3.4						
690-350-01130	R 1.25-3.5 JP	<b>(b) (g</b> (li)		6.6	14.4	6.3				0.8				
690-350-01140	R 1.25-4 JP	<b>(4) (3)</b> (18)		8.0	15.8	7.0			1.7					
690-350-01150	1.25-M4 JP	(h) (£)		6.6	14.4	6.3								
690-350-01160	R 1.25-5 JP	(h) (g) (lis		8.0	15.8	7.0								
690-350-01170	1.25-6 JP	(h) (g)		11.6	21.7	11.1								
690-350-01180	1.25-8 JP	₩ <b>®</b>			21./	11.1								
690-350-01190	2-MS3 JP	3.2	5.5	13.2	5.6	6								
690-350-01200	2-3 JP	(h) (B)		8.5	16.8	7.8	3 3 4.8 3 3	4.1	2.3	0.8	単線:1.14~1.82mm より線:1.04~2.63mm AWG:#16~#14	オープン	1,000個(10箱)	100個 (1箱)
690-350-01210	R 2-3.5 JP	(h) (g) (l)	4.3 6.9 6.9 6.9 6.4 6.4 6.4 6.4	6.6	14.4	6.3								
690-350-01220		<b>(4) (6) (9)</b>		8.5	16.8	7.8								
690-350-01230	+	(h) (f)		6.6	14.4	6.3								
690-350-01240				9.5	16.8	7.3								
690-350-01250	+			8.5		7.8								
690-350-01260				12.0	21.8									
690-350-01270	+													
690-350-01280	+	(h) (f)	5.3	8.0	17.8	9.0		4.8	2.7		単線:— より線:3.5mm AWG:#12			100個
690-350-01290	<del> </del>	(h) (6)					4.8			1.0			1,000個 (10箱)	
690-350-02900	_	(h) (6		10.3	18.6	8.6								(1本日)
690-350-01300 690-350-01310	_		2.6.9 4.3 2.6.9 5.3 2.6.9 5.3 2.6.9 6.4 2.6.9 8.4 2.6.9 8.4 2.6.9 10.5	9.5	19.8	8.3	3.3 6.8							
690-350-01320	_			7.2	15.7	5.9	9 6.2	5.6		1.0	単線: 1.82~2.89mm より線: 2.63~6.64mm AWG: #12~#10		1,000個 (10箱)	100個(1箱)
690-350-01330	_			8.0	19.1	8.3			3.4					
690-350-01340	_	-		9.5	19.8									
690-350-01350	_	USTED (S)			19.1	8.3								
690-350-01360	+	USTED (S) (JS)		12.0	25.8									
690-350-01370	_	USTED (SE		9.0	24.3	13.0	6.8							
690-350-01380	R 5.5-8 JP	(h) (g) (l)		15.0	28.0	13.7	7						3,500個(35箱)	
690-350-01390	5.5-S8 JP	(h) (g)		13.2	22.4	9.0								
690-350-01400	R 5.5-10 JP	<b>(1) (3) (1)</b>		15.0	28.0	13.7								
EW 690-350-02910	5.5-12 JP	(h) (h		19.2	32.4	16.0								
690-350-01410	8-4NS JP	(h) (g)	4.3	8.0	21.8	9.3		T		1.2	単線:2.89~3.65mm より線:6.64~10.52mm AWG:#8		3,500個 (35箱)	100個(1箱)
690-350-01420		₩ <b>®</b>	4.5	12.0	23.8									
690-350-01430	R 8-5 JP	(A) (B) (B)	6.4	12.0	23.8									
690-350-01440	8-5NS JP	(h) (f)		9.0	22.3									
690-350-01450		(h) (f) (l)		12.0	23.8		8.5	7.1	4.5					
690-350-01460		(h) (f)			22.6			/··'	1.5	1.4				
690-350-01470	-	(h) (f) (l)	0.4 (B) 10.5		29.8	13.8								
690-350-01480		(A) (B)		11.5	28.1									
690-350-01490	-	(M) (M) (M)		15.0	_									
EW) 690-350-02920	8-12 JP	(h) (f)	13.0	20.0	33.5	15.0							2,500個 (25箱)	