
裸圧着端子 丸形(R形)14~60









■ 仕 様● 材質:無酸素銅

(I) LISTED E42024	③ LR20812	JQ0608019 / JQID08002 / JQMY14001 / JIS C 2805
----------------------	------------------	--

商品コード	品番	規格	119 / JQID08002 / JQMY14001 / JIS C 2805 寸法(mm))			出荷
			ød ₂	В	L	F	Е	øD	ød ₁	Т	適用電線範囲	標準単価	梱包	出荷 単位
690-350-01500	R 14-5 JP	⊕ ⊕ ⊕	5.3	12.0	29.8									
690-350-01510	14-5NS JP	(h) (f)	6.4 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	9.0	28.3	13.3		.5 9.0			単線:3.65〜4.62mm より線:10.52〜16.78mm AWG:#6		2,500個 (25箱)	100個
690-350-01520	R 14-6 JP			12.0	29.8	13.3			5.8	1.5				
690-350-01530	14-6NS JP	(h) (f)		9.6	28.6									
690-350-01540	R 14-8 JP	(P) (B (II)		16.0	32.8		10.5						(23/11)	(1箱)
690-350-01550	14-8NS JP	(h) (f)		11.5	30.8	14.5								(, , , , ,
690-350-01560	R 14-10 JP			 	32.8									
690-350-01570	R 14-12 JP	<u>⊕</u> ⊕ (18)	-	0 22.0 41.0 19.5							2,000個			
690-350-01580	R 14-14 JP	<u>®</u> ® ⋅ 00	15.0	30.0	49.0	23.5	5					オープン	(20箱)	
690-350-01590	22-S5 JP	(h) (f)			30.0	12.0		11.5	7.7		単線:4.62~5.81mm より線:16.78~26.66mm AWG:#4		1,600個	
690-350-01600	22-5 JP	(h) (f)	5.3	16.5	33.7	13.5							(16箱)	
690-350-01610	22-5NS JP	(h) (£)	USTED SE	9.5	28.7	12.0							2,500個 (25箱)	
690-350-01620	R 22-6 JP	(L) (B (II)	2 6 0.4 12.0 30.0 2 6 0.4 12.0 30.0 2 6 0.4 12.0 30.0 2 6 0.9 10.5 36.7	16.5	33.7	13.5								
690-350-01630	22-S6 JP	(h) (f)		12.0	30.0	12.0	12.0							
690-350-01640	R 22-8 JP	₩ @ ®		16.5	33.7	13.5				1.8			1,600個	100個
690-350-01650	22-S8 JP	(I) (I)		12.0	30.0	12.0				1.0			(16箱)	(1箱)
690-350-01660	R 22-10 JP	(h) (h) (l)		17.5	36.7	16.0								
690-350-01670	22-S10 JP	(h) (f)		16.5	33.7	13.5								
690-350-01680	R 22-12 JP	(h) (g) (JS		22.0	42.5	19.5							1,000個 (10箱)	
690-350-01690	R 22-14 JP	(h) (g) (l)		51.5	24.5							1,600個 (16箱)		
690-350-01700	38-S5 JP	(h) (g	<u>® @</u>	15.5	38.0	16.0			9.4	1.8	単線:5.81~7.34mm より線:26.66~42.42mm AWG:#2		1,200個	
690-350-01710	38-5 JP		0.3 0.5 0.5 0.5 0.5 0.5 0.5		42.7	17.7							(12箱)	
690-350-01720	38-6 JP			22.0	42.7	17.7		13.3						100個
690-350-01730	38-S6 JP	(h) (f)		15.5	38.0	16.0							4.000/15	
690-350-01740	R 38-8 JP	(L) (D (II)	(9) 8.4 22.0 42.7 1 15.5 38.0 1 (9) 10.5 22.0 42.7 1 (9) 13.0 22.0 42.7 1	22.0	42.7	17.7	140							
690-350-01750	38-S8 JP	(h) (g)		15.5	38.0	16.0	7.7 6.0						1,000個(10箱)	(1箱)
690-350-01760	R38-10 JP	⊕ ⊕ ⊕		22.0	42.7	17.7								
690-350-01770	38-S10 JP	(h) (f)		15.5	38.0	16.0								
690-350-01780	R 38-12 JP	₩ G (B)		22.0		17.7								
690-350-01790	R 38-14 JP	LIGHTS -		23.5							1,200個(12箱)			
690-350-01800	60-S6 JP	U) LISTED		16.0	_			15.5	11.4	2.0	単線:7.34~8.26mm より線:42.42~60.57mm AWG:#1/#0			
690-350-01810	R 60-8 JP	(4) (6) (10)	10.5 - 13.0		49.7									
690-350-01820	60-S8 JP	(h) (g		16.0	46.7	20.7							50個	
690-350-01830	R 60-10 JP	(h) (g) (l)			49.7		18.0						1 (1箱)	1個
690-350-01840	60-S10 JP	(h) (g		16.0	46.7								(1/10)	
690-350-01850					49.7		.5							
690-350-01860	R 60-14 JP	(A) (B) (B) (B)	15.0	32.0	57.5	23.5								

01

照 明 **02**

計 測器 **03** 工

具 04 安全用品 05

05 パテープ・ 06

空調部材 07 設備部材

配線器具類 09 配管

08

10 装柱器材 11

盤用資材 12 絶縁処理材

理材 13 電線・ 14 ケーブル類 14 ケーブル類 14 ケーブル類 14 ケーブル類 14 ケーブル類 14 ケーブル類 15 ケーブル 15 ケーブ