

Pan-Ty 形状

- ▶汎用性の高い標準 タイプ
- ▶幅広い用途で使用 可能



- ▶ヘッド及びバンド全体を丸く滑らか に成形
- ▶作業時に手や電線の被覆を傷めない
- ▶ロック爪は頑丈で強度が強く、ストラップは柔軟性が高く、より密着したデザイン

■ 仕 様

- 材質:Non-ULナイロン6.6 (ナチュラル) 耐候性ナイロン6.6 (黒)
- ●使用温度範囲:-60~85℃
- 難燃グレード:UL94V-2相当







図3:Pan-Ty



ナチュラル			結束径 ϕ (mm)		寸法 (mm)						最小ループ 哲量	標進		出荷	
商品コード		形状	最小	最大	L	L1	W	W1	Н	H1	引張強度		単価	梱包	単位
品	番		HX'J'	HX/	-		V V	V V I	""		(IV)				
690-360-09320	690-360-09430	図1	0.8	17	79	3.8	2.3	4.6	0.8	2.9		0.2	-	10袋 (1,000本)	1袋 (100本)
JLB80-100	JLB80B-100										80				
690-360-09330	690-360-09440			22	99	4.3	2.5	1		3.9		03			
JLB100-100	JLB100B-100	Pan-Ty				1.5	2.5		1.1	- 1		0.5			
690-360-09340	690-360-09450		1.5	35	142	5.2	3.6	6.1	1 1	4.6	178	06			
	JLB150B-100				172		5.0	0.1		7.0	170	10.0			
690-360-09350	690-360-09460			51 2	210.8	7.4		8.7	1.2		222	1 1 4			
	JLB200B-100				210.0	7		0.7	1.2	1.2		1			
690-360-09360	690-360-09470		4.1	66	264.2	8.1	5.7	9.1 1	1.3	5.6	334	1 9			
	JLB250B-100											1.5			
690-360-09370	690-360-09480			81	315.0							22			
JLB300-100	JLB300B-100	図2 Super										۷.۷	, ,,		
690-360-09380	690-360-09490	Grip	4.8	105	388.6	10	8.4	13.9	1.6	7.4	534	51		10袋 (500本)	1袋 (50本)
JLB350-50	JLB350B-50]	4.0									J.4			
690-360-09390	690-360-09500		4.1	107	300.0	8.4	5.7	9.1	1.3	5.6	334	2 8		10袋	1袋
JLB370S-100	JLB370SB-100		4.1	107	<u> </u>	0.4	5.7	9.1				2.0		(1,000本)	(100本)
690-360-09400	690-360-09510		4.8	132	471.0	11	9.7	15.2	1.7	8.1	778	77		10袋	1袋
JLB450-50	JLB450B-50		4.0	132	4/1.0	11	9.7	13.2	1./	0.1	//0	最強度 (g/本) 頃本 梱包 単 0.2 0.3 10袋 (1,000本) 10袋 (1,000本) 110 袋 (1000本) 334 1.9 1.9 1.9 1.9 1.9 1.0袋 (500本) 1.50 (500本)<	(50本)		
690-360-09410	690-360-09520	図3	12.7	127	511	16.8	12.7	20.3	1.9	10.2	1,112	1 / 1			1袋
JLB510-25	JLB510B-25											14.1			
690-360-09420	690-360-09530	Pan-Ty		152	564							16 2		(250本)	(25本)
JLB550-25	JLB550B-25											10.5	<u>'</u>		

01 照

明 **02** 計測

03 工

器

04 安全用品 05

05 パテリプ・

06空調部材07

07 設備部材

08 配線器具類

09 配管配線材 10

装柱器材 11 盤用資材

村 12 絶縁処理材

13 電線・

14 ケーブル用