



**MATERIALS**

HOUSING: HI-TEMP. PLASTIC (UL 94V-0)  
 SHELL: COPPER ALLOY, TIN PLATING  
 TERMINAL: COPPER ALLOY, GOLD PLATED

**SPECIFICATION**

CURRENT RATING: 1.8 AMP MAX (ONLY PIN 1, 5),  
 OTHER 1 AMP MAX  
 DIELECTRIC WITHSTANDING: 100V AC FOR ONE MINUTE  
 CONTACT RESISTANCE: 30m OHMS MAX  
 INSULATION RESISTANCE: 100M OHMS MIN AT DC 500V  
 OPERATION TEMPERATURE: -25°C~+85°C

**RoHS Compliant**

TOLERANCES ARE

DRAWING BY CY	X. ±
CHECKED BY GENIUS	.X ± 0.30
UNIT / mm	.XX ± 0.20
SCALE 1 : 1	.XXX ± 0.10
DATE	ANG ±

SIZE A4 PPROJECTION

照片框

**ORDER INFORMATION**

**MISB-SWPR-5B-LF**  
 SERIES | | | | LEADFREE  
 REEL  
 POST  
 90°SMT  
 FEMALE

DESCRIPTION: MICRO USB B TYPE, SMT, WITH POST, 3.8MM, METAL SHIELD, FEMALE