

Specification	ML-40-S1BXF/S	ML-40-S1BYF/S
Rating	250V-10A	
With standing V	AC2000V(1minute)	
Insulation Ω	DC500V,1000M Ω Min	
Safety approvals	UL,CSA	
Number of poles	1 up to 20	1 up to 22
Insulation materials	P.B.T.(UL94V-0)	
Pitch	7.62mm	
Screw	F:Screw with square washer(M3X7.2) ,S:Screw with washer(M3X6)	
Terminal style	PCB	
Body color	Black	
Optional accessories	Name plate:ML-40-3C	-
	Name plate:ML-40-3K	-
	Name plate metal holder:ML-40-3I1 (Need 2 pcs for 1terminal block)	-
	Name plate screw:ML-40-3J (Need 2 pcs for 1terminal block)	-
	Terminal block angled metal holder:ML-40-3L1(Need 2 pcs for 1terminal block)	
	Short circuit metal:ML-1000-3H1,3H2,3H3	
	Banana plug adapter : TJ-3-B-3	
Important notice	Terminal block banana plug:TJ-3-A	
	Except 20 Poles remaining scratch marks at the end due to cutting by pole Must specify when CSA approved products needed	

ML - 40 - S1BX  		
Series	Type	Number of poles
ML - 40	F : Screw with square washer (M3 X 7.2)	1 up to 20
	S : Screw with washer(M3 X6)	

RS Stock No