


APPLICABLE STANDARD				
RATING	OPERATING TEMPERATURE RANGE	- % TO - %	STORAGE TEMPERATURE RANGE	- % TO - %
	VOLTAGE	-	OPERATING HUMIDITY RANGE	- % TO - %
	CURRENT	-	APPLICABLE CABLE	-
SPECIFICATIONS				
ITEM	TEST METHOD	REQUIREMENTS	QT	AT
CONSTRUCTION				
GENERAL EXAMINATION	VISUALLY AND BY MEASURING INSTRUMENT.	ACCORDING TO DRAWING.	X	X
MARKING	CONFIRMED VISUALLY.		X	X
MECHANICAL CHARACTERISTICS				
VIBRATION	FREQUENCY 10 TO 2000 Hz, SINGLE AMPLITUDE 0.75 mm, 98 m/s ² AT 2 h, FOR 3 DIRECTIONS.	NO DAMAGE, CRACK AND LOOSENESS OF PARTS	X	-
SHOCK	490 m/s ² DIRECTIONS OF PULSE 11 ms AT 3 TIMES FOR 6 DIRECTIONS.		X	-
ENVIRONMENTAL CHARACTERISTICS				
CORROSION SALT MIST	EXPOSED IN 5 % SALT WATER SPRAY FOR 48 h.	NO HEAVY CORROSION.	X	-
RAPID CHANGE OF TEMPERATURE	TEMPERATURE -65 ~ 85 °C UNDER 5 CYCLES.	NO DAMAGE, CRACK AND LOOSENESS OF PARTS.	X	-
COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
0				
REMARK Unless otherwise specified, refer to JIS C 5402.		APPROVED	HO.MIWA	06.01.24
		CHECKED	YH.ENAMI	06.01.24
		DESIGNED	TS.ITO	06.01.24
		DRAWN	TS.ITO	06.01.24
Note QT:Qualification Test AT:Assurance Test X:Applicable Test		DRAWING NO.	ELC4-005988-01	
HRS	SPECIFICATION SHEET	PART NO.	P-1660A-CA (50)	
	HIROSE ELECTRIC CO., LTD.	CODE NO.	CL216-0113-9-50	 1/