

P-726

圧着工具 裸圧着端子・裸圧着スリーブ(B・P)用

CRIMPING TOOL

for Bare crimping terminal, sleeve

- トグル機構により単位ストロークあたりの所要握力を軽減しました。握力の弱い方でも、必要な圧着力が楽に得られます。
- 圧着が完了しないとハンドルが開かない成形確認機構つきです。

- The toggle mechanism improves to reduce the squeezing force per the stroke, and even not-so-strong hands can crimp with this tool.
- The ratchet mechanism does not allow the handles to release unless the complete crimp.

ご使用上の注意

△警告

1. 電気が流れている個所には使用しないでください。
2. 成形確認機構を外したり、改造したりしないでください。

△注意

1. 圧着不良が原因で起こる不測の事態について、当社は一切責任を負いかねます。
2. 圧着不良を防ぐために定期的な点検を実施してください。試験成績表のご要望にお応えできるサービス体制を整えています。

長くお使いいただくために

ピンおよび摺動部には定期的に注油してください。摩耗を防ぎ寿命をのばします。各部の摩耗によるガタつきは圧着不良の原因になります。

Precautions

△Warning

1. Do not use on energized places.
2. Do not take apart or not re-model the ratchet Mechanism.

△Caution

1. We are not responsible for any unexpected contingencies due to incomplete crimp.
2. Carry out periodic inspection to prevent incomplete crimp.

Daily care

Lubricate the hinge and the moving parts periodically to prevent wear and prolong their life span. Wear of the moving parts could cause an incomplete crimp.

適合表

Applicability

使用ダイスの呼び Cavity	端子・スリーブの呼称 No. of terminal/sleeve	電線抱合範囲(参考) Applicable wire (Ref.)		
		より線 Stranded mm ²	単線 Single mm φ	AWG
0.3/0.5	0.3/0.5	0.2~0.5	0.35~0.7	26~22
1.25	1.25	0.25~1.65	0.57~1.44	22~16
2.0	2	1.04~2.63	1.14~1.82	16~14

技術的なお問い合わせ

ホーザン ラクニカルホットライン

☎ 06-6567-3132 E-mail: th@hazan.co.jp

【月曜日から金曜日(祝日を除く)の10:30~12:00・13:00~17:00】

補修部品については、web上のパーツリストをご覧ください。

通信販売もご利用いただけます。 [ホーザン 通信販売](#) [検索](#)

ホーザン株式会社

本社 〒556-0021 大阪市浪速区幸町1-2-12
TEL(06)6567-3111 FAX(06)6562-0024

HOZAN TOOL INDUSTRIAL CO.,LTD.

1-2-12 Saiwaicho, Naniwa-ku, Osaka 556-0021, Japan
Tel : +81-6-6567-3111 Fax : +81-6-6562-0024