

PS-10SD-D4C2

Product Details

Part Number	PS-10SD-D4C2
Status	Active
Features	Single-line and double-line connectors available with 2.54mm pitch crimp type, 10 pos., Socket housing
Number of Positions	10 pos.
Contact Pitch (mm)	2.54 mm
Connector Type	Socket housing
Connector Style	
Wire Termination Style	
PCB Mounting Method	
Number of Rows	2
Recommended PCB Thickness (mm)	
Applicable Cable Conductive Area (mm²)	
Applicable Wire Insulation Diameter (mm)	
Dielectric Withstanding Voltage (VACr.m.s. 1minute)	1000
Insulation Resistance (megaohm min.)	1000
Contact Resistance (milliohm max.)	
Material of Contact	

Finish of Contact in Connecting Area	
Finish of Contact in Terminal Area	
Material of Housing	Glass filled PBT (UL94V-0)
Color of Housing	Black
Mounting-side Contact Length (mm)	
Use with Accessories	
Applicable Product Part Numbers	
Crimping Tool	
Packaging Type	
Quantity in The Standard Packaging (pieces)	
Documents	<div style="display: flex; justify-content: space-around; align-items: center;"> <div style="border: 1px solid #ccc; padding: 5px 10px; text-align: center;"> Drawings </div> <div style="border: 1px solid #ccc; padding: 5px 10px; text-align: center;"> PDF Download </div> </div>
Stock Search	<div style="border: 1px solid #ccc; padding: 5px 10px; display: inline-block;"> Stock Search </div>
RoHS compliant	10 substances (2011/65/EU)
REACH compliant	219 substances (08/07/2021)
Environment Information	<div style="border: 1px solid #ccc; padding: 5px 10px; display: inline-block;"> RoHS/Reach Certificate </div>
Combination	PS-10PE-D4LT1-PN1 PS-10PE-D4T1-PN1
Remarks	

Notice

1. The values specified in this web site are only for reference. The products and their specifications are subject to change without notice. Contact our sales staff for further information before considering or ordering any of our products.

For purchase, a product specification must be agreed upon.

2. Users are requested to provide protection circuits and redundancy circuits to ensure safety of the equipment, and sufficiently review the suitability of JAE's products to the equipment.

3. The products presented in this web site are designed for the uses recommended below.

We strongly suggest you contact our sales staff when considering use of any of the products in any other way than the recommended applications or for a specific use that requires an extremely high reliability.

(1) Applications that require consultation:

* Please contact us if you are considering use involving a quality assurance program that you specify or that is peculiar to the industry, such as:

Automotive electrical components, train control, telecommunications devices (mainline), traffic light control, electric power, combustion control, fire prevention or security systems, disaster evention equipment, etc.

* We may separately give you our support with a quality assurance program that you specify, when you think of a use such as :

Aviation or space equipment, submarine repeaters, nuclear power control systems, medical equipment for life support, etc.

(2) Recommended applications include:

* Computers, office appliances, telecommunications devices (terminals, mobile units), measuring equipment, audiovisual equipment, home electric appliances, factory automation equipment, etc