


Rating	16A 125VAC 1/3HP	cULus	Mounting Hole	Circuit Diagram									
	10A 250VAC 1/2HP												
Contact Resistance	50m ohm Max.												
Insulation Resistance	DC 500V 100M ohm Min.												
Dielectric Strength	AC 1500V 1 minute		<table border="1"> <tr> <td>Thickness</td> <td>X</td> <td>Y</td> </tr> <tr> <td>0.75...1.5</td> <td>19.4-0.1</td> <td>13+0.1</td> </tr> <tr> <td>1.5...2.5</td> <td>19.8-0.1</td> <td>13+0.1</td> </tr> </table>	Thickness	X	Y	0.75...1.5	19.4-0.1	13+0.1	1.5...2.5	19.8-0.1	13+0.1	
Thickness	X	Y											
0.75...1.5	19.4-0.1	13+0.1											
1.5...2.5	19.8-0.1	13+0.1											
Operation Temperature	-25°C~85°C												
Switch Function	3P SPST ON-OFF(Illuminated)												



Material:

Frame: Nylon 66 (94-V2)

Actuator: PC clear (94-V2)

Waterproof Rubber: Silicone

Terminals: Silver plated, Copper alloy

Hot stamping: None

Waterproof: IP65

