


|               |  |
|---------------|--|
| Sales Region  | Worldwide  |
| Power Supply  | Single-phase   |
| Series        | RPE  |
| Status        |  Production |
| Features      | Standard type  |
| Option        | <span>Standard</span> Standard type  |
| Option Lineup | <a href="#">Please refer to here.</a>  |
| Accessories   |  |
| Brand         | TDK-Lambda   |



| Electrical Characteristics           |                             |
|--------------------------------------|-----------------------------|
| Rated Current                        | 10A                         |
| Rated Voltage [AC]                   | 250V                        |
| Rated Voltage [DC]                   | 250V                        |
| Withstanding Voltage                 | AC1500V, 60s [line - earth] |
| Insulation Resistance (Min.)         | 100MΩ [DC500V, 1min.]       |
| Leakage Current (Max.)               | 0.5mA [250V, 60Hz]          |
| DC Resistance (Max.)                 | 30mΩ                        |
| Common Mode Attenuation (Min.)       | 25dB (5MHz to 30MHz)        |
| Differential Mode Attenuation (Min.) | 25dB (10MHz to 30MHz)       |

| Package Type & Size |                           |
|---------------------|---------------------------|
| Package / Mounting  | IEC Inlet                 |
| Length(L)           | 50mm Nom. (1.97in Nom.)   |
| Width(W)            | 58.8mm Nom. (2.31in Nom.) |
| Height(H)           | 22.4mm Nom. (0.88in Nom.) |
| Weight              | 40g Typ.                  |

| Other                 |                |
|-----------------------|----------------|
| Terminals             | Tab            |
| Operating Temp. Range | -25 to 85°C    |
| Performance           | Multipurpose   |
| Function              |                |
| Safety Standard       | UL1283         |
|                       | CSA C22.2 No.8 |
|                       | EN60939-1      |
|                       | EN60939-2      |

! Images are for reference only and show exemplary products.  
! This PDF document was created based on the data listed on the TDK Corporation website.  
! All specifications are subject to change without notice.