

TOSHIBA CMOS Digital Integrated Circuit Silicon Monolithic


TC4081BP, TC4081BF, TC4081BFN

TC4081B Quad 2-Input AND Gate

TC4081B is positive logic AND gates with two inputs respectively.


Since all the outputs of these gates are equipped with the buffer circuits of inverters, the input/output propagation characteristic has been improved and variation of propagation time caused by increase of load capacity is kept minimum.

Pin Assignment




Logic Diagram

1/4 TC4081B




Note: xxxFN (JEDEC SOP) is not available in Japan.

TC4081BP




DIP14-P-300-2.54

TC4081BF




SOP14-P-300-1.27A



SOP14-P-300-1.27

TC4081BFN



SOL14-P-150-1.27

Weight

DIP14-P-300-2.54	: 0.96 g (typ.)
SOP14-P-300-1.27A	: 0.18 g (typ.)
SOP14-P-300-1.27	: 0.18 g (typ.)
SOL14-P-150-1.27	: 0.12 g (typ.)

Absolute Maximum Ratings (Note)

Characteristics	Symbol	Rating	Unit
DC supply voltage	V_{DD}	$V_{SS} - 0.5 \sim V_{SS} + 20$	V
Input voltage	V_{IN}	$V_{SS} - 0.5 \sim V_{DD} + 0.5$	V
Output voltage	V_{OUT}	$V_{SS} - 0.5 \sim V_{DD} + 0.5$	V
DC input current	I_{IN}	± 10	mA
Power dissipation	P_D	300 (DIP)/180 (SOIC)	mW
Operating temperature range	T_{ope}	-40~85	°C
Storage temperature range	T_{stg}	-65~150	°C

Note: Exceeding any of the absolute maximum ratings, even briefly, lead to deterioration in IC performance or even destruction.

Recommended Operating Conditions ($V_{SS} = 0$ V) (Note)

Characteristics	Symbol	Test Condition	Min	Typ.	Max	Unit
DC supply voltage	V_{DD}	—	3	—	18	V
Input voltage	V_{IN}	—	0	—	V_{DD}	V

Note: The recommended operating conditions are required to ensure the normal operation of the device. Unused inputs must be tied to either VCC or GND.

Static Electrical Characteristics ($V_{SS} = 0\text{ V}$)

Characteristics		Sym- bol	Test Condition	V_{DD} (V)	-40°C		25°C			85°C		Unit
					Min	Max	Min	Typ.	Max	Min	Max	
High-level output voltage		V_{OH}	$ I_{OUT} < 1\text{ }\mu\text{A}$ $V_{IN} = V_{SS}, V_{DD}$	5	4.95	—	4.95	5.00	—	4.95	—	V
				10	9.95	—	9.95	10.00	—	9.95	—	
				15	14.95	—	14.95	15.00	—	14.95	—	
Low-level output voltage		V_{OL}	$ I_{OUT} < 1\text{ }\mu\text{A}$ $V_{IN} = V_{SS}, V_{DD}$	5	—	0.05	—	0.00	0.05	—	0.05	V
				10	—	0.05	—	0.00	0.05	—	0.05	
				15	—	0.05	—	0.00	0.05	—	0.05	
Output high current		I_{OH}	$V_{OH} = 4.6\text{ V}$	5	-0.61	—	-0.51	-1.0	—	-0.42	—	mA
			$V_{OH} = 2.5\text{ V}$	5	-2.50	—	-2.10	-4.0	—	-1.70	—	
			$V_{OH} = 9.5\text{ V}$	10	-1.50	—	-1.30	-2.2	—	-1.10	—	
			$V_{OH} = 13.5\text{ V}$	15	-4.00	—	-3.40	-9.0	—	-2.80	—	
			$V_{IN} = V_{DD}$									
Output low current		I_{OL}	$V_{OL} = 0.4\text{ V}$	5	0.61	—	0.51	1.2	—	0.42	—	mA
			$V_{OL} = 0.5\text{ V}$	10	1.50	—	1.30	3.2	—	1.10	—	
			$V_{OL} = 1.5\text{ V}$	15	4.00	—	3.40	12.0	—	2.80	—	
			$V_{IN} = V_{SS}, V_{DD}$									
Input high voltage		V_{IH}	$V_{OUT} = 0.5\text{ V}, 4.5\text{ V}$	5	3.5	—	3.5	2.75	—	3.5	—	V
			$V_{OUT} = 1.0\text{ V}, 9.0\text{ V}$	10	7.0	—	7.0	5.50	—	7.0	—	
			$V_{OUT} = 1.5\text{ V}, 13.5\text{ V}$	15	11.0	—	11.0	8.25	—	11.0	—	
			$ I_{OUT} < 1\text{ }\mu\text{A}$									
Input low voltage		V_{IL}	$V_{OUT} = 0.5\text{ V}, 4.5\text{ V}$	5	—	1.5	—	2.25	1.5	—	1.5	V
			$V_{OUT} = 1.0\text{ V}, 9.0\text{ V}$	10	—	3.0	—	4.50	3.0	—	3.0	
			$V_{OUT} = 1.5\text{ V}, 13.5\text{ V}$	15	—	4.0	—	6.75	4.0	—	4.0	
			$ I_{OUT} < 1\text{ }\mu\text{A}$									
Input current	"H" level	I_{IH}	$V_{IH} = 18\text{ V}$	18	—	0.1	—	10^{-5}	0.1	—	1.0	μA
	"L" level	I_{IL}	$V_{IL} = 0\text{ V}$	18	—	-0.1	—	-10^{-5}	-0.1	—	-1.0	
Quiescent supply current		I_{DD}	$V_{IN} = V_{SS}, V_{DD}$ (Note)	5	—	0.25	—	0.001	0.25	—	7.5	μA
				10	—	0.50	—	0.001	0.50	—	15.0	
				15	—	1.00	—	0.002	1.00	—	30.0	


Note: All valid input combinations.

Dynamic Electrical Characteristics (Ta = 25°C, V_{SS} = 0 V, C_L = 50 pF)


Characteristics	Symbol	Test Condition		Min	Typ.	Max	Unit
			V _{DD} (V)				
Output transition time (low to high)	t _{TLH}	—	5	—	70	200	ns
			10	—	35	100	
			15	—	30	80	
Output transition time (high to low)	t _{THL}	—	5	—	70	200	ns
			10	—	35	100	
			15	—	30	80	
Propagation delay time	t _{pLH}	—	5	—	65	200	ns
			10	—	30	100	
			15	—	25	80	
Propagation delay time	t _{pHL}	—	5	—	65	200	ns
			10	—	30	100	
			15	—	25	80	
Input capacitance	C _{IN}	—	—	—	5	7.5	pF

Circuit and Waveform for Measurement of Dynamic Characteristics

Circuit




Waveform



Package Dimensions

DIP14-P-300-2.54

Unit : mm




Weight: 0.96 g (typ.)

Package Dimensions


SOP14-P-300-1.27A

Unit: mm



Weight: 0.18 g (typ.)

Package Dimensions




Weight: 0.18 g (typ.)

Package Dimensions (Note)

SOL14-P-150-1.27

Unit : mm



Note: This package is not available in Japan.

Weight: 0.12 g (typ.)

Note: Lead (Pb)-Free Packages**DIP14-P-300-2.54 SOP14-P-300-1.27A SOL14-P-150-1.27****RESTRICTIONS ON PRODUCT USE**

060116EBA

- The information contained herein is subject to change without notice. 021023_D
- TOSHIBA is continually working to improve the quality and reliability of its products. Nevertheless, semiconductor devices in general can malfunction or fail due to their inherent electrical sensitivity and vulnerability to physical stress. It is the responsibility of the buyer, when utilizing TOSHIBA products, to comply with the standards of safety in making a safe design for the entire system, and to avoid situations in which a malfunction or failure of such TOSHIBA products could cause loss of human life, bodily injury or damage to property.
In developing your designs, please ensure that TOSHIBA products are used within specified operating ranges as set forth in the most recent TOSHIBA products specifications. Also, please keep in mind the precautions and conditions set forth in the "Handling Guide for Semiconductor Devices," or "TOSHIBA Semiconductor Reliability Handbook" etc. 021023_A
- The TOSHIBA products listed in this document are intended for usage in general electronics applications (computer, personal equipment, office equipment, measuring equipment, industrial robotics, domestic appliances, etc.). These TOSHIBA products are neither intended nor warranted for usage in equipment that requires extraordinarily high quality and/or reliability or a malfunction or failure of which may cause loss of human life or bodily injury ("Unintended Usage"). Unintended Usage include atomic energy control instruments, airplane or spaceship instruments, transportation instruments, traffic signal instruments, combustion control instruments, medical instruments, all types of safety devices, etc. Unintended Usage of TOSHIBA products listed in this document shall be made at the customer's own risk. 021023_B
- The products described in this document shall not be used or embedded to any downstream products of which manufacture, use and/or sale are prohibited under any applicable laws and regulations. 060106_Q
- The information contained herein is presented only as a guide for the applications of our products. No responsibility is assumed by TOSHIBA for any infringements of patents or other rights of the third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of TOSHIBA or others. 021023_C
- The products described in this document are subject to the foreign exchange and foreign trade laws. 021023_E