APPLICA	BLE STANI	DARD								
	OPERATING TEMPERATURE RANGE				STORAGE	DE DANIGE				
RATING					TEMPERATU CHARACTER					
	POWER				IMPEDANCE					
			SPECI	IFICAT	IONS					
ITEM			TEST METHOD			REQUIREMENTS			QT	AT
CONSTRUCTION GENERAL EVAMINATION			WAND DV MEACUIDING INCTRUMENT			ACCORDING TO DRAWING.				1
			VISUALLY AND BY MEASURING INSTRUMENT. CONFIRMED VISUALLY.			DING TO D	RAVVING	э.	X	
WARKING		CONFIRMED VISUALLY.							X	X
COUNT	T. DE	EQCRIPTI	ON OF BEVISIONS		ESIONED			CHECKED		ATE.
COUN	T DE	ESCRIPTI	ON OF REVISIONS	D	ESIGNED			CHECKED	D,	ATE
A REMARK						APPROV	EDI	HO.MIWA	ne	10.27
I SERVICE CONTRACTOR OF THE PROPERTY OF THE PR						CHECKE		HO.MIWA	_	10.27
						DESIGNI		SJ.SHIMIZU	_	10.27
Unless otherwise specified, refer t			fer to JIS C 5402.	r to JIS C 5402.		DRAWN		SJ.SHIMIZU		10.27
Note QT:Qualification Test AT:Assurance Test X:Applicable Test					DRAWIN	L		ELC4-043523-01		
HS		SPECIFICATION SHEET			ART NO.	TM-8-DC1				
	HIR	OSE E	SE ELECTRIC CO., LTD.			CL222-2261-9-00			⚠	1/1