



成形品寸法 Size of molded goods	公差 Tolerances
$L \leq 4$	$\pm 0.2$
$4 < L \leq 15$	$\pm 0.3$
$15 < L \leq 30$	$\pm 0.5$
$30 < L \leq 50$	$\pm 0.8$

材質: 6ナイロン  
UL94V-2

※穴径のみ公差は0~+0.1

品番	穴径	板厚	φd	L	φD	A	抜去力(Kgf)
TPR2024-BK	2.1	0.6~1.2	2.0	2.4	4.2	1.2	3
TPR2024-W	2.1	0.6~1.2	2.0	2.4	4.2	1.2	3
TPR2032-BK	2.1	1.3~2.0	2.0	3.2	4.2	1.2	3
TPR2032-W	2.1	1.3~2.0	2.0	3.2	4.2	1.2	3
TPR2040-BK	2.1	2.1~2.8	2.0	4.0	4.2	1.2	3
TPR2040-W	2.1	2.1~2.8	2.0	4.0	4.2	1.2	3
TPR2048-BK	2.1	2.9~3.6	2.0	4.8	4.2	1.2	3
TPR2048-W	2.1	2.9~3.6	2.0	4.8	4.2	1.2	3
TPR2064-BK	2.1	3.7~4.4	2.0	6.4	4.2	1.2	3
TPR2064-W	2.1	3.7~4.4	2.0	6.4	4.2	1.2	3
TPR2632-BK	2.7	1.0~2.0	2.6	3.2	5.0	1.4	5
TPR2632-W	2.7	1.0~2.0	2.6	3.2	5.0	1.4	5
TPR2642-BK	2.7	2.1~3.0	2.6	4.2	5.0	1.4	5
TPR2642-W	2.7	2.1~3.0	2.6	4.2	5.0	1.4	5
TPR2648-BK	2.7	2.7~3.6	2.6	4.8	5.0	1.4	5
TPR2648-W	2.7	2.7~3.6	2.6	4.8	5.0	1.4	5
TPR2655-BK	2.7	3.4~4.3	2.6	5.5	5.0	1.4	5
TPR2655-W	2.7	3.4~4.3	2.6	5.5	5.0	1.4	5

品番	穴径	板厚	φd	L	φD	A	抜去力(Kgf)
TPR3035-BK	3.1	1.0~2.0	3.0	3.5	6.4	1.6	8
TPR3035-W	3.1	1.0~2.0	3.0	3.5	6.4	1.6	8
TPR3045-BK	3.1	2.0~3.0	3.0	4.5	6.4	1.6	8
TPR3045-W	3.1	2.0~3.0	3.0	4.5	6.4	1.6	8
TPR3055-BK	3.1	3.0~4.0	3.0	5.5	6.4	1.6	8
TPR3055-W	3.1	3.0~4.0	3.0	5.5	6.4	1.6	8
TPR3065-BK	3.1	4.0~5.0	3.0	6.5	6.4	1.6	8
TPR3065-W	3.1	4.0~5.0	3.0	6.5	6.4	1.6	8
TPR3075-BK	3.1	5.0~6.0	3.0	7.5	6.4	1.6	8
TPR3075-W	3.1	5.0~6.0	3.0	7.5	6.4	1.6	8
TPR3080-BK	3.1	5.5~6.5	3.0	8.0	6.4	1.6	8
TPR3080-W	3.1	5.5~6.5	3.0	8.0	6.4	1.6	8
TPR3090-BK	3.1	6.5~7.5	3.0	9.0	6.4	1.6	8
TPR3090-W	3.1	6.5~7.5	3.0	9.0	6.4	1.6	8
TPR3100-BK	3.1	7.5~8.5	3.0	10.0	6.4	1.6	8
TPR3100-W	3.1	7.5~8.5	3.0	10.0	6.4	1.6	8

作成日 2018.6.20	検図 東京商品部	TRUSCO トラスコ中山株式会社	品名 樹脂製プッシュリベット	品番 TPR0000-00
------------------	-------------	-------------------	-------------------	------------------