



成形品寸法 Size of molded goods	公差 Tolerances
$L \leq 4$	± 0.2
$4 < L \leq 15$	± 0.3
$15 < L \leq 30$	± 0.5
$30 < L \leq 50$	± 0.8

材質:6ナイロン
UL94V-2

※穴径のみ公差は0~+0.1

品番	穴径	板厚	φd	L	φD	A	抜去力(Kgf)
TPR3535-BK	3.6	1.2~2.1	3.5	3.5	6.4	1.6	12
TPR3535-W	3.6	1.2~2.1	3.5	3.5	6.4	1.6	12
TPR3545-BK	3.6	2.2~3.1	3.5	4.5	6.4	1.6	12
TPR3545-W	3.6	2.2~3.1	3.5	4.5	6.4	1.6	12
TPR3550-BK	3.6	2.7~3.6	3.5	5.0	6.4	1.6	12
TPR3550-W	3.6	2.7~3.6	3.5	5.0	6.4	1.6	12
TPR3555-BK	3.6	3.2~4.1	3.5	5.5	6.4	1.6	12
TPR3555-W	3.6	3.2~4.1	3.5	5.5	6.4	1.6	12
TPR3560-BK	3.6	3.7~4.6	3.5	6.0	6.4	1.6	12
TPR3560-W	3.6	3.7~4.6	3.5	6.0	6.4	1.6	12
TPR3570-BK	3.6	4.7~5.6	3.5	7.0	6.4	1.6	12
TPR3570-W	3.6	4.7~5.6	3.5	7.0	6.4	1.6	12
TPR3580-BK	3.6	5.7~6.6	3.5	8.0	6.4	1.6	12
TPR3580-W	3.6	5.7~6.6	3.5	8.0	6.4	1.6	12
TPR4040-BK	4.1	1.4~2.4	4.0	4.0	8.0	1.8	20
TPR4040-W	4.1	1.4~2.4	4.0	4.0	8.0	1.8	20
TPR4050-BK	4.1	2.5~3.5	4.0	5.0	8.0	1.8	20
TPR4050-W	4.1	2.5~3.5	4.0	5.0	8.0	1.8	20
TPR4060-BK	4.1	3.5~4.5	4.0	6.0	8.0	1.8	20
TPR4060-W	4.1	3.5~4.5	4.0	6.0	8.0	1.8	20
TPR4070-BK	4.1	4.5~5.5	4.0	7.0	8.0	1.8	20
TPR4070-W	4.1	4.5~5.5	4.0	7.0	8.0	1.8	20
TPR4080-BK	4.1	5.5~6.5	4.0	8.0	8.0	1.8	20
TPR4080-W	4.1	5.5~6.5	4.0	8.0	8.0	1.8	20

品番	穴径	板厚	φd	L	φD	A	抜去力(Kgf)
TPR4090-BK	4.1	6.5~7.5	4.0	9.0	8.0	1.8	20
TPR4090-W	4.1	6.5~7.5	4.0	9.0	8.0	1.8	20
TPR4100-BK	4.1	7.5~8.5	4.0	10.0	8.0	1.8	20
TPR4100-W	4.1	7.5~8.5	4.0	10.0	8.0	1.8	20
TPR4120-BK	4.1	9.5~10.5	4.0	12.0	8.0	1.8	20
TPR4120-W	4.1	9.5~10.5	4.0	12.0	8.0	1.8	20
TPR5045-BK	5.1	1.5~2.5	5.0	4.5	9.0	2.2	25
TPR5045-W	5.1	1.5~2.5	5.0	4.5	9.0	2.2	25
TPR5055-BK	5.1	2.5~3.5	5.0	5.5	9.0	2.2	25
TPR5055-W	5.1	2.5~3.5	5.0	5.5	9.0	2.2	25
TPR5065-BK	5.1	3.5~4.5	5.0	6.5	9.0	2.2	25
TPR5065-W	5.1	3.5~4.5	5.0	6.5	9.0	2.2	25
TPR5075-BK	5.1	4.5~5.5	5.0	7.5	9.0	2.2	25
TPR5075-W	5.1	4.5~5.5	5.0	7.5	9.0	2.2	25
TPR5085-BK	5.1	5.5~6.5	5.0	8.5	9.0	2.2	25
TPR5085-W	5.1	5.5~6.5	5.0	8.5	9.0	2.2	25
TPR5095-BK	5.1	6.5~7.5	5.0	9.5	9.0	2.2	25
TPR5095-W	5.1	6.5~7.5	5.0	9.5	9.0	2.2	25
TPR5105-BK	5.1	7.5~8.5	5.0	10.5	9.0	2.2	25
TPR5105-W	5.1	7.5~8.5	5.0	10.5	9.0	2.2	25
TPR6060-BK	6.1	2.5~4.0	6.0	6.0	12.0	2.5	30
TPR6060-W	6.1	2.5~4.0	6.0	6.0	12.0	2.5	30
TPR6080-BK	6.1	4.0~5.5	6.0	8.0	12.0	3.0	30
TPR6080-W	6.1	4.0~5.5	6.0	8.0	12.0	3.0	30

作成日

2018.6.20

検図

東京商品部

TRUSCO トラスコ中山株式会社

品名

樹脂製プッシュリベット

品番

TPR0000-00