



4	高効率電動機搭載 EQUIPPED WITH HIGHLY EFFECTIVE ELECTRIC MOTOR		
3	吸込 溶接金網付 (4メッシュ d0.7) WITH SUCTION WIRE NET (4 MESH d0.7)		
2	電 動 機 M O T O R	保護方式 ENCLOSURE	全閉外扇形 TOTALLY ENCLOSED FAN COOLED TYPE
		出力 OUTPUT	[kW] 0.4
		極数・相 POLES・PHASE	2・3
		周波数 FREQUENCY	[Hz] 50 60
		電圧 VOLTAGE	[V] 200 200/220
		IEコード又は効率基準 IE CODE OR EFFICIENCY STANDARD	76.0% 77.0%
1	送 風 機 F A N	風量 (MAX.) VOLUME	[m³/min] 8.5 5.9
		静圧 (MAX.) [kPa] STATIC PRESSURE	3.00 4.30
		回転数 SPEED	[min⁻¹] 2900 3450
		標準吸込状態 STANDARD SUCTION CONDITION	温度 TEMPERATURE 20℃ 相対湿度 HUMIDITY 65% 絶対圧力 ABSOLUTE P. 101.3 kPa
仕 様 SPECIFICATIONS			

作成 DRAW	S. HATANO	作成日 DATE	2012. 3. 1 MARCH 1, 2012
尺度 SCALE	1:5	品名 TYPE	U75-H3-R313
確認 承認 APPROVE	S. HATANO M. TANAKA	図名 TITLE	外形寸法図 EXTERNAL DIMENSIONS
昭和電機株式会社 大東工場 SHOWA DENKI CO., LTD DAITO FACTORY		図番 DRAWING NO.	YU45R31300-0

図 歴 RECORDS	変更日 DATE	変更内容 REVISION	変更 REVISED BY
△×			
△×			
△×			