



**PCB.LAYOUT**  
TOL:±0.05

**备注:**

- 电气性能:
- 接触阻抗: 50 毫欧 (最大)
- 绝缘阻抗: 100 兆欧 (最小)
- 耐高压: 100V AC 一分钟
- 胶芯耐高温: 265 °C
- 材料:
- 胶芯: LCP
- 端子: 磷铜C5191
- 外壳: C2680/SPCC
- 电镀:
- 端子: 接触区域镀半金1/3u", 焊接区域镀亮锡100-200u"
- 外壳: 全区域镀镍50-80u"

TOLERANCE UNLESS OTHERWISE SPECIFIED  
XXX ±0.10  
.XX ±0.20  
.X ±0.30  
.X ±3°

产品名称  
PART NAME:  
MINI 5P/F 90度两脚

料号  
PART No.:

USB-027

REV:	DESCRIPTION	REV BY	APPROVED	DATE	MATL:	SEE SPECIFICATION	APPROVED
					PROJECTION:	THIRD ANGLE PROJECTION	CHECKED
					UNIT:	SHEET	DRAWN
B	更新料号	LiTao		2011.04.01	MM	1 OF 1	DATE
					SCALE	1:1	
					REV (NO)	A	
					DATE	2011.04.01	
					DRAWN	LiTao	
					1 OF 1		