



- Material : polyolefin
- Color : Black. Other colors available on request
- Recognition : recognized under UL224 and CSA standard, rating voltage 600V, VW-1at 125°C
- Environment protection
- Feature : insulation or jacketing of wire harness , insulation of wire terminals, capsule of electronic components, identification or colorcoding of wires
- Special length available on request

UNIT : mm

Item No.	As supplied		After shrinkage		Packing
	INSIDE DIAMETER MIN	WALL THICKNESS NOMINAL	INSIDE DIAMETER MAX	WALL THICKNESS NOMINAL	
125°C UL CSA					
K32-1	1.4±0.2	0.2	0.5	0.33	200 M
K32-1.5	2.0±0.2	0.2	0.75	0.36	
K32-2	2.5±0.2	0.2	1.0	0.44	
K32-2.5	3.0±0.2	0.25	1.25	0.44	
K32-3	3.5±0.3	0.25	1.5	0.44	
K32-3.5	4.0±0.3	0.25	1.75	0.44	
K32-4	4.5±0.3	0.25	2.0	0.44	
K32-5	5.4±0.3	0.25	2.5	0.56	100 M
K32-6	6.4±0.4	0.25	3.0	0.56	
K32-7	7.4±0.4	0.25	3.5	0.56	
K32-8	8.4±0.4	0.25	4.0	0.56	50 M
K32-9	9.4±0.4	0.25	4.5	0.56	
K32-10	10.4±0.4	0.25	5.0	0.56	
K32-11	11.4±0.4	0.25	5.5	0.56	
K32-12	12.4±0.4	0.25	6.0	0.56	
K32-13	13.5±0.4	0.3	6.5	0.69	
K32-14	14.5±0.4	0.3	7.0	0.69	
K32-15	15.5±0.5	0.3	7.5	0.69	
K32-16	16.8±0.5	0.3	8.0	0.69	
K32-18	18.7±0.5	0.35	9.0	0.77	
K32-20	21.2±0.6	0.35	10.0	0.77	
K32-22	23.2±0.6	0.4	11.0	0.77	
K32-25	26.1±0.8	0.4	12.5	0.87	
K32-28	29.0±1.0	0.5	14.0	0.87	
K32-30	32.0±1.0	0.5	15.0	0.87	
105°C UL					
FZ-35	37±1.0	0.5	17.5	0.87	30 M
FZ-40	43.0±1.5	0.5	20.5	0.97	
FZ-50	53.0±2.0	0.5	25.0	0.97	
FZ-60	60min.	0.55	30.0	1.07	
FZ-80	80min.	0.6	40.0	1.17	
FZ-100	100min	0.6	50.0	1.17	

# HEAT-SHRINKABLE TUBINGS

VALUE PACK



## VS-100

### CONTENTS:

K32-1.5	3.5cm	RD, BE, WE, YW @5pcs
K32-2.5	3.5cm	RD, BE, WE, YW @5pcs
K32-3.5	3.5cm	RD, BE, WE, YW @5pcs
K32-5	3.5cm	RD, BE, WE, YW @5pcs
K32-7	7.5cm	RD, WE @3pcs BE, YW @2pcs
K32-10	7.5cm	RD, WE, YW @1pcs, BE 2pcs
K32-13	7.5cm	RD, WE, YW @1pcs, BE 2pcs

## VS-100BK

### CONTENTS:

K32-1.5	3.5cm	20pcs
K32-2.5	3.5cm	20pcs
K32-3.5	3.5cm	20pcs
K32-5	3.5cm	20pcs
K32-7	7.5cm	10pcs
K32-10	7.5cm	5pcs
K32-13	7.5cm	5pcs