



品番	呼び径	ピッチ	長さ l	φ dt (最大)	e (最小)	S
Y301-0303	M3	0.5	3	0.3	1.73	1.5
Y301-0304	M3	0.5	4	0.3	1.73	1.5
Y301-0305	M3	0.5	5	0.3	1.73	1.5
Y301-0306	M3	0.5	6	0.3	1.73	1.5
Y301-0308	M3	0.5	8	0.3	1.73	1.5
Y301-0310	M3	0.5	10	0.3	1.73	1.5
Y301-0404	M4	0.7	4	0.4	2.30	2.0
Y301-0405	M4	0.7	5	0.4	2.30	2.0
Y301-0406	M4	0.7	6	0.4	2.30	2.0
Y301-0408	M4	0.7	8	0.4	2.30	2.0
Y301-0410	M4	0.7	10	0.4	2.30	2.0
Y301-0505	M5	0.8	5	0.5	2.87	2.5
Y301-0506	M5	0.8	6	0.5	2.87	2.5
Y301-0508	M5	0.8	8	0.5	2.87	2.5
Y301-0510	M5	0.8	10	0.5	2.87	2.5
Y301-0512	M5	0.8	12	0.5	2.87	2.5
Y301-0525	M5	0.8	25	0.5	2.87	2.5
Y301-0606	M6	1.0	6	1.5	3.44	3.0
Y301-0608	M6	1.0	8	1.5	3.44	3.0
Y301-0610	M6	1.0	10	1.5	3.44	3.0
Y301-0612	M6	1.0	12	1.5	3.44	3.0

材質: SUS XM-7相当

単位: mm

作成日 2020.06.19

検図

TRUSCO トラスコ中山株式会社

品名 六角穴付止めねじとがり先 ステンレス

品番 Y301-※※※※