



形式	適合電線管	標準パッキン 内径 (mm)	適合ケーブル範囲 (mm)	寸法 (mm)					質量 (g)		
				d	B ₁	B ₂	S ₁	S ₂		L	
EX16B	C	16 (PF 1/2)	9	7~9	12.5	26	28	19	15	79	180
	D		11	9~11							
	E		12	11~12							
EX22B	C	22 (PF 3/4)	13	11~13	16.5	32	34	19	15	81	260
	D		15	13~15							
	E		16	15~16							
EX28B	C	28 (PF 1)	18	16~18	21	38	40	24	19	91	390
	D		19	17~19							
	E		20	19~20							
EX36B	C	36 (PF 1 1/4)	22	20~22	27	46	49	24	19	91	550
	D		24	22~24							
	E		26	24~26							
EX42B	C	42 (PF 1 1/2)	26	24~26	31	52	55	25	19	98	740
	D		28	26~28							
	E		30	28~30							
EX54B	C	54 (PF 2)	32	30~32	39	65	68	26	21	112	1270
	D		34	32~34							
	E		36	34~36							
	F		38	36~38							
EX70B	C	70 (PF 2 1/2)	40	38~40	50	82	85	28	23	122	2400
	D		42	40~42							
	E		44	42~44							
	F		46	44~46							
	G		48	46~48							
EX82B	C	82 (PF 3)	50	48~50	58	96	100	28	25	139	3500
	D		52	50~52							
	E		54	52~54							
	F		56	54~56							

061117

6	ロックナット	鋼材	1	電気亜鉛メッキ	品名	耐圧防爆形ケーブルグランド				
	5	グランド	黄銅	1		ニッケルメッキ	保護管接続用			
4	クランプ	ステンレス	1		質量	—	単位	mm	尺度	N
	3	座金	鋼板	1		電気亜鉛メッキ	EIS000980-1			
2	パッキン	クロロプレナム	1		図番					
1	本体	黄銅	1	ニッケルメッキ						
部番	部品名	材質・材厚	数	備考						