



RoHS 10

P2をご確認下さい

品番	各部の寸法 mm							電線抱合範囲		適用工具		包装個数	
	φd2	B	L	S	F	E	φD	φd	燃線mm ²	AWGor MCM	手動工具 本体 ヘッド		
CB 22-5S ○	5.3	12.5	31.0	5.5	13.5	12.0	11.6	7.7	16.78	4	NOP 60 NOM60 NOP 150HA NOM 150 NA 20 N20 22	100	
CB 22-6S ○	6.4			6.4	12.6				26.66				
CB 22-8S ○	8.2			6.4	12.6				26.66				
CB 38-5S ○	5.3	13.5	36.8	7.5	16.3	13.0	13.4	9.4	26.66	2	NOP 60 NOM 60 NOP 150HA NOM 150 NA 20 N20 38	100	
CB 38-6N ○	6.4	12.5	34.8	5.5					42.42				
CB 38-6S ○	6.4	13.5	36.8	7.5					42.42				
CB 38-8N	8.4	12.5	34.8	7.4	14.4								
CB 60-6N ○	6.4	16.0	46.5	8.0	20.0	18.5	15.6	11.4	42.42	1/0	NOP 60 NOM 60 NOP 150HA NOM 150 NA 20 N20 60 NOP 700 NOM 2500A NOM 3000	100	
CB 60-6S ○			49.5	11.0					60.57				
CB 60-8 ▲○	8.4		46.5	8.0					60.57				
CB 60-8S ○	8.4	49.5	11.0	60.57									
CB 60-10S ○	10.5												
CB 70-6	6.4	20.5	51.0	12.0	20.0	19.0	17.8	13.5	60.57	2/0	NOP 150HA NOM 150 NOP 700 NOM 2500A NOM 3000	25	
CB 70-8	8.4								76.28				
CB 70-10	10.5								76.28				
CB 70-12	13.0								76.28				
CB 80-8	8.4	22.0	50.0	11.0	20.0	19.0	19.6	14.5	76.28	3/0	NOP 150HA NOM 150 NOP 700 NOM 2500A NOM 3000	50	
CB 80-8S			49.0	10.0					96.3				
CB 80-10	10.5		50.0	11.0					96.3				
CB 80-10S	10.5		49.0	10.0					96.3				
CB 80-12S	13.0												
CB 100-8 ▲	8.4	22.0	52.0	11.0	22.0	19.0	22.5	16.4	96.3	4/0	NOP 150HA NOM 150 NOP 700 NOM 2500A NOM 3000	50	
CB 100-8S			53.0	12.0					117.2				
CB 100-10 ▲	10.5		52.0	11.0					117.2				
CB 100-10S	10.5		53.0	12.0					117.2				
CB 100-12S	13.0												
CB 150-8 ▲	8.4	22.0	60.3	11.0	22.3	27.0	26.6	19.5	117.2	250- 300 MCM	NOP 150HA NOM 150 NOP 700 NOM 2500A NOM 3000	20	
CB 150-8S			61.3	12.0					152.05				
CB 150-10S	10.5		25.0	61.8					12.5				152.05
CB 150-10 ▲	10.5		22.0	61.3					12.0				152.05
CB 150-12S	13.0												
CB 200-10S	10.5	36.0	72.0	19.0	22.3	30.7	32.9	24.0	192.6	400 MCM	NOP 700 NOM 2500A NOM 3000	NOH 300K	
CB 200-12S	13.0								242.27				
CB 250-8	8.4	40.0	81.2	17.0	31.0	33.2	35.6	26.5	250	—	NOP 700 NOM 2500A NOM 3000	*NOH 300K	
CB 250-10	10.5								250				
CB 250-12	13.0								250				
CB 325-12S	13.0	38.5	85.5	17.0	32.0	36.5	37.8	28.0	242.27	500- 600 MCM	NOP 700 NOM 2500A NOM 3000	NOH 300K	
CB 325-12		44.0							325				

注1) ▲：JEM規格該当品（日本電機工業会規格） ○：UL・CSA登録品

- 2) [UL・CSA登録品] [電線被覆ムキ寸法] についてはP14をご覧ください。
- 3) *NOH 300Kで250mm²端子を圧着される場合は325mm²端子用のダイスをご使用下さい。
- 4) 250mm²端子はREC-Li250M（マクセルイズミ製）もご使用頂けます。