

LS 14500

3.6 V primary lithium thionyl chloride (Li-SOCl₂) High Energy Density bobbin AA-size cell



For applications requesting good voltage response and operating life in -60/+85°C environments.

Cell size references

UM3 - R6 - AA

Electrical characteristics

(typical values for cells stored for one year or less)

Nominal capacity 2.25 Ah
(at 2 mA +20°C 2 V cut off. The capacity restored by the cell varies according to current drain, temperature and cut off)

Open circuit voltage (at +20°C) 3.67 V

Nominal voltage (at 0.2 mA +20°C) 3.6 V

Pulse capability : Typically up to 25 mA. (Varies according to pulse characteristics, temperature, cell history and the application's acceptable minimum voltage. Fitting the cell with a capacitor may be recommended in severe conditions. Consult Saft)

Continuous current permitting 50% of the nominal capacity to be achieved at +20°C with 2 V cut off. 100 mA
(Higher currents possible, consult Saft)

Storage (recommended) +30°C max
(for more severe conditions, consult Saft)

Operating temperature range -60/+85°C
(Operation above ambient T may lead to reduced capacity and lower voltage readings at the beginning of pulses. Consult Saft)

Other characteristics

Li metal content		approx. 0.6 g
Diameter (max)		14.65 mm (0.58 in)
Height (max)		50.3 mm (1.98 in)
Typical weight		16.2 g
Available termination suffix	CN, CNR 2 PF, 3 PF, 3 PF RP, 4 PF CNA (AX) FL	radial tabs radial pins axial leads flying leads ...etc.

Key features

- High and stable operating voltage
- Low self discharge rate
(less than 1% after 1 year of storage at +20°C)
- Stainless steel container and end caps
(low magnetic signature)
- Hermetic glass-to-metal sealing
- Non-flammable electrolyte
- Compliant with IEC 86-4 safety standard and EN 50020 intrinsic safety
- Underwriters Laboratories (UL) Component Recognition
(File Number MH 12609)
- Non-restricted for transport

Main applications

- Utility metering
- Automatic meter reading
- Alarms and security devices
- Tollgate systems
- Memory back-up
- Tracking systems
- Automotive electronics
- Professional electronics
... etc.