

LS 17500

3.6 V primary lithium thionyl chloride (Li-SOCl₂) High Energy Density bobbin A-size cell



For applications requesting good voltage response and operating life in –60/+85°C environments.

Cell size reference

A

Electrical characteristics

(typical values for cells stored for one year or less)

Nominal capacity 3.4 Ah

(at 4 mA +20°C 2 V cut off. The capacity restored by the cell varies according to current drain, temperature and cut off)

Open circuit voltage (at +20°C) 3.67 V

Nominal voltage (at 0.3 mA +20°C) 3.6 V

Pulse capability : Typically up to 35 mA. (Varies according to pulse characteristics, temperature, cell history and the application's acceptable minimum voltage. Fitting the cell with a capacitor may be recommended in severe conditions. Consult Saft)

Continuous current permitting 50% of the nominal capacity to be achieved at +20°C with 2 V cut off. (Higher currents possible, consult Saft) 130 mA

Storage (recommended) +30°C max
(for more severe conditions, consult Saft)

Operating temperature range –60/+85°C

(Operation above ambient T may lead to reduced capacity and lower voltage readings at the beginning of pulses. Consult Saft)

Other characteristics

Li metal content approx. 0.9 g

Diameter (max) 17.0 mm (0.67 in)

Height (max) 50.9 mm (2.00 in)

Typical weight 21.9 g

Available termination suffix	CN, CNR	radial tabs
	2 PF, 3 PF, 3 PF RP, 4 PF	radial pins
	CNA (AX)	axial leads
	FL	flying leads ...etc.

Key features

- High and stable operating voltage
- Low self discharge rate (less than 1% after 1 year of storage at +20°C)
- Stainless steel container and end caps (low magnetic signature)
- Non-flammable electrolyte
- Underwriters Laboratories (UL) Component Recognition (File Number MH 12609)
- Compliant with IEC 86-4 safety standard and EN 50020 intrinsic safety
- Non-restricted for transport

Main applications

- Utility metering
- Automatic meter reading
- Alarms and security devices
- Tollgate systems
- Identification tags
- Tracking systems
- Automotive electronics
- Professional electronics ... etc.