



All dimensions are in mm; tolerances according to ISO 2768 m-H

Interface

Mechanically compatible with RPC-1.85

Documents

Assembly instruction 02 A3

Material and plating

Connector parts

- Center contact
- Outer contact
- Coupling nut
- Dielectric
- Solder sleeve

Material

- Beryllium copper
- Stainless steel
- Stainless steel
- PEEK
- Brass

Plating

- Gold, min. 1.27 µm, over chemical nickel
- Passivated
- Passivated
- Gold, 0.1 µm min.

Electrical data

Impedance	50 Ω
Frequency	DC to 50 GHz
Return loss	≥ 23 dB, DC to 50 GHz
Insertion loss	≤ 0.05 x √f(GHz) dB
Insulation resistance	≥ 5 GΩ
Center contact resistance	≤ 4.0 mΩ
Outer contact resistance	≤ 2.5 mΩ
Test voltage	500 V rms
Working voltage	150 V rms
RF-leakage	≥ 100 dB up to 1 GHz

- Limitations are possible due to the used cable type -

Mechanical data

Mating cycles	≥ 500
Center contact captivation	≥ 20 N
Coupling test torque	1.65 Nm
Recommended torque	0.80 Nm to 1.10 Nm

Environmental data

Temperature range	-40°C to +85°C
Thermal shock	IEC 61169-1, Subclause 9.4.4
Corrosion	IEC 61169-1, Subclause 9.4.6
Vibration	IEC 61169-1, Subclause 9.3.3
Shock	IEC 61169-1, Subclause 9.3.14
Moisture resistance	IEC 61169-1, Subclause 9.4.3
2002/95/EC (RoHS)	compliant

Tooling

N/A

Suitable cables

UT 85 / RTK-FS 085 / RTK-Flex 405

Packing

Standard	1 pce in bag
Weight	9.2 g/pce

While the information has been carefully compiled to the best of our knowledge, nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. In the effort to improve our products, we reserve the right to make changes judged to be necessary.

Draft	Date	Approved	Date	Rev.	Engineering change number	Name	Date
Herbert Babinger	26/08/04	Krautenbacher J.	19/10/06	b00	06-0478	Wallner Markus	19/10/06
Rosenberger Hochfrequenztechnik GmbH & Co. KG P.O.Box 1260 D-84526 Tittmoning Germany www.rosenberger.de					Tel.: +49 8684 18-0 Fax: +49 8684 18-499 email: info@rosenberger.de		Page 2 / 2