


ITEM NO.	PART NUMBER	DESCRIPTION	QTY.	COMPONENT NOTES
1	50-00426	Connector, USB B receptacle	1	
2	50-00433	Connector, USB B mini male	1	
3	30-00088	Wire, 4C, 1PR + 2C, 28 AWG, UL2725, 30V, 80C, 3.6 mm, shielded, VW-1, PVC, 79A, USB 2.0	1	
4	24-00057	Overmold, PVC, black	1	
5	24-00025	Overmold, PVC, black	1	
6	Label 660	Adhesive, flag, 10x60 mm	1	



Notes:
Cables individually tied and bundled in groups of 10
Functionally equivalent components may be substituted

Wiring diagram		
50-00426	Wire Color	50-00433
1	Red	1
2	White	2
3	Green	3
4	Black	5
Shell	Drain & Shield	Shell

Revision:	Date:	Description:	Prepared:	Notes:	<h1>TENSILITY</h1> <p>tel 1.541.323.3228 800 877.670.7118 fax 1.541.323.4202 web tensility.com</p>
A	8/24/2011	Initial release		RoHS and REACH compliant	
A1	1/28/2014	Corrected shield type	Verified:	Function test: no open, no short circuit, no intermittent	
A2	6/30/2016	Corrected barrel length		Description:	Size: A
			Dimensions are in millimeters. Tolerances: X: ± 0.5 mm X.X: ± 0.3 mm X.XX: ± 0.05 mm	Cable, 100 mm, USB B receptacle to USB mini B 5P male, 28 AWG, 30-00088 wire	Part number: 10-00660
					Scale: 1:1
					Sheet 1 of 1