


ITEM NO.	PART NUMBER	DESCRIPTION	QTY.	COMPONENT NOTES
1	TLY-1P	NEMA 1-15P, polarized	1	black overmold
2	30-00242	2C, 18 AWG, UL SPT-1, 300V, 105C, 5.55 mm, VW-1, PVC	1	



Wire marking: (UL) E339575 SPT-1 2x0.824 mm2
 (18AWG) 105C 300V VW-1 C(UL) SPT-1 2x0.824 mm2
 (18AWG) 105C 300 V VW-1 Tensility HLE

SECTION A-A
 SCALE 2 : 1

Wiring Diagram	
1-15P	wire
hot	smooth
neutral	ribbed

Notes:
 Electrical requirements: 10 A at 125 Vac

Revision:	Date:	Description:	Prepared:	Notes: RoHS and REACH compliant	<h1>TENSILITY</h1> tel 1.541.323.3228 800 877.670.7118 fax 1.541.323.4202 web tensility.com
A	12/17/2012	Initial release	Verified:		
			Dimensions are in millimeters. Tolerances: X: ± 0.5 mm X.X: ± 0.3 mm X.XX: ± 0.05 mm	Description: Ac cord, 1000 mm, U.S, NEMA 1-15P plug, TLY-1P to tinned, 18 AWG, SPT-1 wire, 30-00242	Size: A Part number: 11-00018
					Scale: 1:1 Sheet 1 of 1