

# PIN RECEPTACLES

**FOR .048" - .064" DIAMETER PINS (#13 CONTACT)  
FOR .045" - .065" DIAMETER PINS (#23 CONTACT)**

<p><b>8365</b> <b>8365-0-15-XX-13-XX-10-0</b> Hex press-fit in .106 plated through-hole</p>	<p><b>8996</b> <b>8996-0-31-XX-13-XX-04-0</b> Compliant press-fit in .040 ± .003 plated hole. For .060" → .100" thick board</p>	<p><b>9064</b> <b>9064-0-15-XX-13-XX-10-0</b> Solder mount in .102 min. mounting hole Also available on 16mm wide carrier tape: 1,300 parts per 13" reel Order as: 9064-0-57-XX-13-XX-10-0</p>	<p><b>9280</b> <b>9280-0-15-XX-13-XX-10-0</b> Solder mount in .102 min. mounting hole</p>
<p><b>8347</b> <b>8347-0-15-XX-13-XX-10-0</b> Solder mount in .109 min. mounting hole</p>	<p><b>4900</b> <b>4900-0-19-XX-23-XX-10-0</b> Swage mount in .067 hole</p>	<p><b>0716</b> <b>0716-0-33-XX-23-XX-10-0</b> Wire crimp termination. Accepts wire sizes 16 AWG Max. / 20 AWG Min.</p>	<p><b>0760</b> <b>0760-0-18-XX-13-XX-10-0</b> Press-fit in .106 mounting hole For wire sizes up to 16 AWG</p>

**SPECIFICATIONS:**

**Shell Material:** Brass Alloy 360, 1/2 Hard  
**Contact Material:** Beryllium Copper Alloy 172, HT  
**Dimensions:** Inches  
**Tolerances On:** Lengths: ± .005  
Diameters: ± .002  
Angles: ± 2°



**ORDER CODE: XXXX - X - XX - XX - XX - XX - 0**

**BASIC PART #**

**SPECIFY SHELL FINISH:**

- 01 200 μ" TIN/LEAD OVER NICKEL
- ◆ 80 200 μ" TIN OVER NICKEL (RoHS)
- ◆ 15 10 μ" GOLD OVER NICKEL (RoHS)

**SPECIFY CONTACT FINISH:**

- 01 200 μ" TIN/LEAD OVER NICKEL
- ◆ 80 200 μ" TIN OVER NICKEL (RoHS)
- ◆ 27 30 μ" GOLD OVER NICKEL (RoHS)

**SELECT CONTACT:**

**#13 or #23 CONTACT (DATA ON PAGE 260)**  
(For alternate contact choices, see group G on page 248)

